

कमांक:- विकास/ 981 (5) कार्यालय जोधपुर नगर निगम

दिनांक:- 10/8/020

निविदा सूचना

(यूनिक विड संख्याDLB2021W50B10316.....)

नगर निगम जोधपुर की ओर से निम्नलिखित कार्य हेतु भारत सरकार एवं राज्य सरकार के विभिन्न विभागों/स्वायत्तशापी/निगमों/बोर्डों/राजकीय उपक्रमों में पंजीकृत ए.0ए व ए. श्रेणी में पंजीकृत तथा नगर निगम जोधपुर में निर्धारित श्रेणी में पंजीकृत नियमानुसार योग्य संवेदको से निर्धारित प्रपत्र में मुहरबन्द निविदा आमत्रित की जाती है। निविदा दिनांक 17-8-020 को 12:30 बजे तक बेची जाकर, दिनांक 17-8-020 को दोपहर 2:00 बजे तक प्राप्त कर 3:00 बजे उपस्थित संवेदको के समक्ष खोली जायेगी। अन्य विवरण एवं शर्त निविदा प्रपत्र कार्यालय समय में कार्यालय में देखे जा सकते हैं। www.sppp.raj.nic.in एवं जोधपुर नगर निगम की वेबसाई www.jodhpurmc.org पर देखी जा सकती है।


| क्र. सं. | कार्य का नाम | अनु. लागत लाखों में | धरोहर राशि | निविदा शुल्क | कार्य पूर्ण करने की अवधि |
|----------|---|---------------------|------------|--------------|--------------------------|
| 01 | इंदिरा रसोई के लिए वार्ड 10 में दीनदयाल उपाध्याय पार्क में निर्मित हॉल में रंग रोगन व मरम्मत का कार्य | 1.50 | 3000/- | 500/- | 7 days |


नोट :- (1) दरे 30 दिवस तक मान्य होगी। (2) कार्य शुरू करने से पूर्व व कार्य पूर्ण करने के पश्चात् कार्य स्थल की फोटो/ विडियोग्राफी सी0डी0 आवश्यक रूप से प्रस्तुत करें। (3) सशर्त निविदा स्वीकार नहीं होगी। (4) दोष निवारण अवधि नियमानुसार होगी। (5) धरोहर राशि के डिमाण्ड ड्राफ्ट की वैधता निविदा खोलने की तारीख से निविदा की वैधता अवधि तक होनी अनिवार्य है अन्यथा निविदा कॉपी निरस्त की जा सकती है। (6) निविदा कॉपी बाबत् आवेदन पत्र के साथ पंजीयन व जीएसटी प्रमाण-पत्र संलग्न करना आवश्यक है, अन्यथा निविदा कॉपी जारी नहीं की जायेगी।

कमांक:- विकास/ 982-88

प्रतिलिपी :- सूचनार्थ एवं आवश्यक कार्यवाही हेतु।

1. श्रीमान जिला कलेक्टर महोदय, जोधपुर।
2. निदेशक/अधीक्षण अभियन्ता, स्थानीय निकाय विभाग, जयपुर।
3. अधीक्षण अभियन्ता/अधिशापी अभियन्ता, सा.नि.वि./जोधपुर विकास प्राधिकरण/नगर निगम जोधपुर।
4. लेखाधिकारी, जोधपुर नगर निगम ।
5. निविदा क्षेत्रीय समाचार पत्र दैनिक प्रतिनिधि में प्रकाशन हेतु।
6. ओसवाल डाटा प्रोसेसर को भेजकर लेख है कि निविदा सूचना पोर्टल संख्या.तुरन्त प्रभाव से अधिशापी अभियन्ता को प्रस्तुत करे एवं निविदा सूचना निगम की वेबसाईट (1) www.sppp.raj.nic.in व (3) www.jodhpurmc.org पर अपलोड करने हेतु।
7. सूचना पट्ट जोधपुर नगर निगम।


आयुक्त
जोधपुर नगर निगम
दिनांक:- 10/8/020


आयुक्त
जोधपुर नगर निगम

OFFICE OF THE MUNICIPAL CORPORATION, JODHPUR

NIT No. date

Last Date of Sale :-

Earnest Money : Rs.

Date of Receipt :-

CR No. Dated.

Copy issued to M/s

G-sch.

Rate Based on RUIDP 2017

Name of Work:- Renovation Of Indra rasoi in Dindayal Upadhay at ward no -10 jodhpur

| S.No. | item no | Particulars | Qty. | Unit | Rate | Amount |
|-------|---------|---|-------|------|---------|---------|
| 1 | 2.4.5.2 | Dismantling of existing structures like culverts, bridges, retaining walls, CC road and other structure comprising of masonry, cementconcrete, wood work, steel work, including T&P and scaffolding wherever necessary, sorting the dismantled material, disposal of unserviceable material and stacking the serviceable material with alllifts and lead of 50 metres as directed by Engineer.Rubble stone masonry in cement mortar. | | | | |
| | | | 0.86 | CUM | 256.00 | 218.88 |
| 2 | 13.2.2 | Random rubble stone masonry work in cement mortar with mechanical mixer in foundation (at any level) complete as per drawing and technical specification and as per clause 1000 and 1400 of MoRT&H specification including all scaffolding materia l, labour, machinery but excluding pointing and plastering. walls, CC road and other structure comprising of masonry, cement concrete, wood work, steel work, including T&P and scaffolding wherever necessary, sorting the dismantled material, disposal of unserviceable material and stacking the serviceable material with all lifts and lead of 50 metres as directed by Engineer.Rubble stone masonry in cement mortar.In cement mortar 1:4 (1 cement : 4 coarse sand) | | | | |
| | | Total QTY | 1.44 | cum | 3530.00 | 5083.20 |
| 3 | 32.8&9 | Cement plastering including T&P, scaffolding, material and complete labpour, including cost of water, curing, racking of joints etc. with 6 mm cement plaster 1:3 (1 cement : 3 fine sand) finished with a floating coat of neat cement and thick coat of Lime wash on top of walls when dry for bearing of R.C.C. slabs and beams. | | | | |
| | | Total QTY | 29.91 | Sqm | 201.00 | 6011.51 |
| 4 | 29.2 | Structural steel work riveted, bolted or welded in built up sections,trusses and framed work, including cutting, hoisting, fixing in position and applying a priming coat of approved steel primer all complete | | | | |
| | | Total QTY | 80.00 | KG | 69.00 | 5520.00 |
| 5 | 26.15.1 | Stone work (machine cut edges) for wall lining upto 10 m height etc. (Veneer work) backing filled with a grout of 12mm thick cement mortar 1:3 (1 Cement : 3 coarse sand) and jointed with Cement mortar 1:2 (1 cement : 2 stone dust) including rubbing and polishing complete. (To be secured to the backing by means of cramps which shall be paid for separately) Kota stone slabs exposed face dressed and rubbed. | | | | |

| | | | | | | |
|----|----------|---|--------------|------------|----------------|-----------------|
| | | Total QTY | 14.58 | Sqm | 1700.00 | 24786.00 |
| 6 | 32.22.1 | Pointing on stone work with cement mortar 1:3 (1 cement : 3 fine sand) :Flush/ Ruled pointing | | | | |
| | | | 25.91 | sqm | 141.00 | 3653.03 |
| 7 | 32.30.1 | Distemping with oil bound washable distemper of approved brand and manufacture to give an even shade New work (two or more coats) over and including priming coat with cement primer. | | | | |
| | | | 324.28 | sqm | 86.00 | 27888.32 |
| 8 | 32.33.1 | Finishing walls with water proofing cement paint of required shade New work (Two or more coats applied @ 3.84 kg/10 sqm). | | | | |
| | | | 25.91 | sqm | 55.50 | 1437.89 |
| 9 | 32.50.1 | Painting with synthetic enamel paint of approved brand and manufacture to give an even shade :Two or more coats on new work | | | | |
| | | | 90.72 | Sqm | 69.00 | 6259.68 |
| 10 | 33.5.1 | Renewing glass panes, with putty and nails wherever necessary Float glass panes of thickness 4 mm | | | | |
| | | | 10.80 | Sqm | 637.00 | 6879.60 |
| 11 | 37.1.1.1 | Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/ appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixed with rawl plugs and screws or with fixing clips, or with expansion hold fasteners including necessary filling up of gaps at junctions, at top, bottom and sides with required PVC/neoprene felt etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / panelling, C.P. brass / stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge. (Glazing and panelling to be paid for separately) : | | | | |
| | | Anodised aluminium (anodised transparent or dyed to required shade according to IS: 1868, Minimum anodic coating of grade AC 15) | | | | |
| | | | 40.00 | kg | 357.00 | 14280.00 |
| 12 | 37.1.2.1 | For shutters of doors, windows & ventilators including providing and fixing hinges/ pivots and making provision for fixing of fittings wherever required including the cost of PVC / neoprene gasket required (Fittings shall be paid for separately). Anodised aluminium (anodised transparent or dyed to required shade according to IS: 1868, Minimum anodic coating of grade AC 15) | 8.00 | kg | 383.00 | 3064.00 |

| | | | | | | |
|----|--------|---|-------|-------|-----------------|------------------|
| 13 | 37.7.2 | Providing and fixing machine moulded aluminium covering of approved pattern & design, made out of machine cut aluminium sheet and machine holed for receiving screws, over expansion joints on vertical surfaces/ceilings with full threaded, cadmium plated steel screws 4mm dia. stem, 30mm long and aluminium washers 2mm thick, 15mm dia. at a staggered pitch of 200mm centre to centre including drilling holes in the receiving surface and providing expandable plastic sleeves in holes etc. complete. Powder coated aluminium sheet 2.5mm thick (minimum thickness of powder coating 50 micron) | 12.00 | kg | 469.00 | 5628.00 |
| 14 | 37.2.2 | Providing and fixing 12mm thick Pre-laminated particle board flat pressed three layer or graded wood particle board conforming to IS: 12823 Grade I Type II, in panelling fixed in aluminium doors, windows shutters and partition frames with C.P. brass / stainless steel screws etc. complete as per architectural drawings and directions of engineer-in-charge | | | | |
| | | Pre-laminated particle board with decorative lamination on both sides. | | | | |
| | | | 1.44 | Sqm | 892.00 | 1284.48 |
| 15 | 1.39.2 | P&F extension pipe for bib cocks of approved quality/ make: C.P. brass of Heavy & superior quality 100x15mm | 2.00 | Point | 79.00 | 158.00 |
| 16 | | | 10.00 | mtr | 152.00 | 1520.00 |
| 17 | | P & F PVC storage Tank conforming to (IS : 12701/89) Standards of approved make with cover, 25mm dia 1M long G.I. over flow pipe & 25cm. Long wash out pipe with plug & socket. Including making connection etc. complete of approved design 1000 (litres capacity) | 1.00 | Each | 6900.00 | 6900.00 |
| 18 | | Providing and fixing G.I. pipes complete with G.I. fittings and clamps, including cutting and making good the walls etc. Internal work - Exposed on wall (a) 15mm dia nominal bore | 15 | Mtr. | 199.00 | 2985.00 |
| | | (b) 25mm (---do---) | 50.00 | Mtr. | 292.00 | 14600.00 |
| 19 | | Providing and fixing PTMT Ball cock of approved quality, colour and make complete with Epoxy coated aluminium rod with L.P./ H.P.H.D. plastic ball. 15 mm nominal bore, 105 mm long. Weighing not less than 138 gms. | 1.00 | Each | 153.00 | 153.00 |
| 20 | | Supplying & fixing 560mm dia SFRC manhole cover as per IS : 12592-2002 in existing manholes frame complete in all respect as directed by the Engineer. | 1.00 | Nos. | 1570.00 | 1570.00 |
| 21 | 29.5.1 | Providing and fixing 1mm thick M.S. sheet door with frame of 40x40x6mm angle iron and 3mm M.S. gusset plates at the junctions and corners, all necessary fittings complete, including applying a priming coat of approved steel primer. Using M.S. angels 40x40x6 mm for diagonal braces. | 2.52 | Sqm | 2790.00 | 7030.80 |
| 22 | 1201 | Stainless steel kitchen sink - with drain board bowl depth 250 mm. | 1.00 | Nos. | 2600.00 | 2600.00 |
| | | | | | Total Rs | 149511.39 |

SAY in lacs 1.50