

# जोधपुर नगर निगम, (दक्षिण)

पोलिटैनिनक कॉलेज परिसर, रेजीडेन्सी रोड, जोधपुर  
E-Mail- ceo nnj@rediffmail.com, nnjelectrical@gmail.com Tel: 0291 2651464

क्रमांक - सं./एफ-15/कार्य/2024/RL-13947

दिनांक 05/07/2024

ई- निविदा सूचना क्रमांक RL-13941 दिनांक 05/07/2024

UBN No. DLB2425WSOB02563

जोधपुर नगर निगम दक्षिण द्वारा इच्छुक कार्यो के अनुगवी/गोप्यताकारी विहित निकाय लाईसेन्सधारी संवेदको, नगर निगम मे पञ्जीकृत नियमानुसार E-EWSD श्रेणी सवेदको, अन्य निकाय मे पञ्जीकृत E-EWSD-I ऑन-लाईन ई- टेंडर प्रक्रिया से निगम शर्तो के अधीन निविदाये आमत्रित की गये है निविदा के कार्यो, गोप्यता, शर्तो की समस्त जानकारी वेबसाईट पर [www.eproc.raj.in](http://www.eproc.raj.in) अथवा [www.sppp.raj.nic.in](http://www.sppp.raj.nic.in) अथवा <https://lsg.rajasthan.gov.in/MCJS> पर देखी जा सकती है।

(डॉ. टी शुभमंगला)

I.A.S

आयुक्त

नगर निगम, (दक्षिण) जोधपुर

क्रमांक- सं./एफ-15/कार्य/2024/RL-13948 जो 13952

प्रतिलिपि

दिनांक- 05/07/2024

1. राजस्थान संवाद जोधपुर को भेज कर लेख है कि आगामी अंक में एक राज्य स्तरीय संस्करण एवं जोधपुर संस्करण में प्रकाशित कर बिल भुगतान हेतु प्रस्तुत करे।
2. दिल लिपिक, नगर निगम, जोधपुर।
3. ऑसवाल डाटा जोधपुर। इस निविदा [www.sppp.raj.nic.in](http://www.sppp.raj.nic.in) वेब साईट पर अपलोड करावे।
4. मैसर्स, इलीट मंत्रा, JMC वेब साईट पर अपलोड करावे।
5. नोटिस बोर्ड नगर निगम जोधपुर।

आयुक्त

नगर निगम, (दक्षिण) जोधपुर

RajKaj Ref  
8695111



Signature valid

Digitally signed by T  
Shubhamangala  
Designation : Commissioner  
Date: 2024.07.05 16:18:01 IST  
Reason: Approved

Scanned by CamScanner

Scanned with CamScanner

# जोधपुर नगर निगम, (दक्षिण)

भोलोटेक्निक कॉलेज परिसर, रेजीडेन्सी रोड, जोधपुर  
E-Mail- ceo\_nnj@rediffmail.com, nnjelectrical@gmail.com Tel: 0291-2651464

क्रमांक - रा / एफ / 15 / कार्य / 2024 / **RL-1394**

दिनांक 05/07/2024

ई निविदा सूचना

UBN No DLB2425WSOB02563

जोधपुर नगर निगम दक्षिण द्वारा इन्वोक कार्यों के अनुगो/सायतावासी डिजिटल विद्युत उपकरण-संग्रहण एवं सेवा नगर निगम में पंजीकृत नियमानुसार श्रेणी सदस्यों के अन्य विभाग में पंजीकृत EEWSD-1 ऑन लाईन ई-टेंडर प्रोसेसिंग के माध्यम से शर्तों के अधीन निविदा आमंत्रित की जाती है। निविदा की शर्तें लेखा नियमानुसार होगी।

क्र	कार्य का नाम	अनुमानित लागत (लाखों में)	अमानित राशि 2%	ई-टेंडर प्रोसेसिंग शुल्क	निविदा प्रपत्र शुल्क	कार्य करने की अवधि
1	Supply And Stringing of Phase Wire in ward (78-80) Jmc South	7.50	15000	500	500	6 माह
2	Supply And Stringing of road light phase wire in ward No (38-77) JMC South	7.00	14000	500	500	6 माह
3	Electrification Work from Sardarpura Thana to Children Park in JMC south Zone (2) Jodhpur	10.74	21480	500	500	6 माह
4	Supplying And Fixing of SHM in ward (38-80) South Jodhpur	8.4	16800	500	500	6 माह
5	Supply and fixing of LED in ward 38 to 80 in MCJS	30.29	60580	500	500	12 माह
6	Supplying and fixing of LED in ward 80 JMC South	5.99	11980	500	500	6 माह
7	Supplying and fixing of LED in ward 78 in JMC South	12.40	24800	500	500	6 माह
8	Supply and Fixing of LED street light in ward 1 to 37 in MCJS	30.29	60580	500	500	12 माह

निविदा प्रकाशित करने की तिथि	दिनांक 06/07/2024
निविदा अपलोड करने की तिथि	दिनांक 08/07/2024 से 17/07/2024 दिनांक
निविदा डाउनलोड/अपलोड करने की अंतिम तिथि व समय	दिनांक 17/07/2024 अपराह्न 6:00 PM तक
निविदा के दस्तावेज कार्यालय में जमा कराने की दिनांक	दिनांक 18/07/2024 अपराह्न 12:00 PM तक
निविदा खोलने की तिथि व समय	दिनांक 18/07/2024 अपराह्न 2:00 PM तक

ई-निविदा प्रपत्रों को वेब साइट <http://eproc.rajasthan.gov.in> से अपलोड डाउनलोड किया जा सकता है। इन निविदाओं में भाग लेने वाले सदस्यक निविदा को इलेक्ट्रॉनिक फारमेट में वेबसाइट पर <http://eproc.rajasthan.gov.in> जमा कराए। विस्तृत विवरण एवं शर्तों के लिए नगर निगम दक्षिण कार्यालय के विद्युत अनुभाग से जानकारी प्राप्त की जा सकती है। ई निविदा की महत्वपूर्ण शर्तें निम्नानुसार हैं-

- आर.टी.पी.पी. एक्ट 2012 एवं आर.टी.पी.पी. रूल्स 2013 के नियम एवं शर्तें निविदा में लागू होंगे।
- निविदा प्रपत्र शुल्क व धरोहर राशि का डिमाण्ड ड्राफ्ट आयुक्त नगर निगम जोधपुर दक्षिण payable जोधपुर होना चाहिए। निविदा जारी के पश्चात दिनांक की डी.डी. प्रस्तुत करनी होगी अन्यथा निविदा से निरस्त कर दी जायेगी।
- वित्त विभाग के आदेश अनुसार ई-टेंडर प्रोसेसिंग शुल्क 5000 लाख रुपये तक की राशि के कार्य के लिए 500/- व 50.00 लाख रुपये से अधिक राशि के कार्य के लिए 1500/- रु की राशि निविदा शुल्क के अतिरिक्त देनी होगी जो डिमाण्ड या बैंकर के रूप में देय होगी। यह डिमाण्ड ड्राफ्ट या बैंकर चेक MD, RISL, payable at Jaipur होना चाहिए।
- निविदाकर्ता द्वारा निविदा शुल्क, धरोहर राशि, E-Tender प्रोसेसिंग राशि डिमाण्ड ड्राफ्ट की प्रति सम्बन्धित कार्यालय में जमा कराना आवश्यक होगा।

RajKaj Ref  
8695130



Signature valid

Digitally signed by T  
Shubhamangala  
Designation: Commissioner  
Date: 2024.07.05 16:17:54 IST  
Reason: Approved

Scanned by CamScanner

Scanned with CamScanner



18 यदि निविदादाता 11वीं तारीख तक ही पुर्ण समय पर नहीं कर पाये प्रस्ताव प्रदर्शक द्वारा ई-प्रोसिसिंग प्रणाली पर निविदादाता को जमाने से मना कर दिया है तो 5000/- रु प्रतिदिन की दर से जुमाना जायेगा एवं ब्याज अग्रिम राशि से कटौत कर लिया जायेगा।

19 कार्य की प्रगतिवस्था की देखी जाए प्रस्ताव पर भी अग्रिम दिख जायेगा यदि ब्याज अग्रिम राशि से कटौत कर लिया जायेगा।

20 तकिएर के काम का निष्पन्न करने की अवस्था में कार्य निष्पन्न हो गयेगा यदि कार्य प्रगतिवस्था में अग्रिम दिख जायेगा अन्यथा कार्य प्रगतिवस्था में अग्रिम दिख जायेगा।

21 इस करार के अन्तर्गत समस्त विवादों तथा इस करार के निर्वान से संबंधित समस्त प्रश्नों का निष्पन्न होना होगा।

22 सिविल विवाद की स्थिति में स्थानीय सिविल न्यायालय को ही हो अधिकार होगा।

23 समस्त समस्त कार्य निष्पन्न करने तक समय समय पर कार्य प्रगतिवस्था में अग्रिम दिख जायेगा।

24. निविदा प्रिफ्लिट एड्स की मूल्य की निम्नानुसार प्रतिशत के प्रकार पर नकली मूल्य होगा:-
- सिविल परियोजना कार्याधी के एक चौथाई कात्वाधी तक विलम्ब 2.50 प्रतिशत
  - सिविल कार्याधी से एक चौथाई से अधिक किन्तु आधी से अनाधेन कात्वाधी तक विलम्ब 5.00 प्रतिशत
  - सिविल कार्याधी के आधी से किन्तु तीन चौथाई तक भी कात्वाधी का विलम्ब 7.50 प्रतिशत
  - सिविल कार्याधी के तीन चौथाई से अधिक की कात्वाधी का विलम्ब 10.00 प्रतिशत
  - निर्धारित सुकसान की अधिकतम रकम 10.00 प्रतिशत।

25. निविदादाता को ई-नेज़ द्वारा सूचना दी जा सकती है। इसलिए आप अपने वाटरमार्क नक्शे, ई-प्रोसिसिंग प्रणाली पर अपलोड कर ली जायेगी।

26. संतोषजनक कार्य नहीं होने की स्थिति में अनुबंध को किसी भी समय निरस्त किया जा सकता है।

27. निविदादाता द्वारा किसी भी आर्टम की दर प्रस्तुत नहीं करने पर निविदा को अपूर्ण मानकर निरस्त कर दिया जायेगा।

28. यदि किसी निविदादाता द्वारा टेण्डर की राशि से कम दर भरी जाती है तो सफल निविदादाता को एलआए अग्रिम प्रदान जारी किया जाने के 14 दिवस के अन्दर के अन्दर अन्तर की राशि बीजी/एफडीआर/एनएससी के रूप में समस्त निम्न म जमा करानी होगी। कार्य संतोषप्रद पूर्ण होने के पश्चात वापस लौटा दी जायेगी।

29. निविदादाता द्वारा निविदा प्रपत्र तथा एनेक्सवर को स्वयं हस्ताक्षर कर रफेन करके <http://eproc rajasthan gov.in> पर अपलोड करने पर ही निविदा को मान्य किया जायेगा। अन्यथा निविदा निरस्त कर दी जायेगी।

30. निविदादाता दरों की दृढता अवधि खोले जाने की दिनांक से 90 दिवस तक अनुमोदन हेतु मान्य होगी।

31. कार्य की दाय निवारण अवधि 02 वर्ष की रहेगी जिसमें किसी प्रकार की लापरवाही बरतने पर दित से कर्तव्य नभ्य देनेसे की जाएगी जिसकी समस्त जिम्मेदारी आप स्वयं की रहेगी।

32. संवेदक को RUIDP - 2023 के नियमानुसार Annexure के अनुसार करवाना होगा, जिस पर होने वाला व्यय संवेदक द्वारा वहन किया जाएगा, नियम द्वारा इस संबंध में कोई भी राशि देय नहीं होगी।

33. ई-टेंडरिंग के लिए निविदादाता हेतु निर्देश:-

- (अ) इन निम्नलिखितों में दिलचरपी लेने वाले निविदादाता निविदा प्रपत्रों का इन्टरनेटसाईट <http://eproc.rajasthan.gov.in> से डाउनलोड कर सकते हैं
- (ब) निविदाओं में भाग लेने वाले निविदादाताओं का इन्टरनेट साईट <http://eproc.rajasthan.gov.in> पर रजिस्टर करवाना होगा। ऑन लाईन निविदा में भाग लेने के लिए डिजिटल सर्टिफिकेट इनफोनेरेशन टेक्नोलोजी एक्ट 2000 के तहत प्राप्त करना होगा। जो इलेक्ट्रॉनिक निविदा में साइन करने हेतु काम आयेगा। निविदादाता उपरोक्त डिजिटल सर्टिफिकेट सी.सी.ए द्वारा स्वीकृति एजेन्सी से प्राप्त कर सकते हैं। जिन निविदादाताओं के पास पूर्व में वैध डिजिटल सर्टिफिकेट सी.सी.ए द्वारा स्वीकृति एजेन्सी से प्राप्त कर सकते हैं। जिन निविदादाताओं के पास पूर्व में वैध डिजिटल सर्टिफिकेट है, नया डिजिटल सर्टिफिकेट लेने की आवश्यकता नहीं है।

RajKaj Ref  
8695130

**Signature valid**

Digitally signed by T  
Shubhamangala  
Designation : Commissioner  
Date: 2024.07.05 16:17:54 IST  
Reason: Approved

Scanned by CamScanner

- (स) भिविदा प्रणाली को भिविदा पोर्टल इलेक्ट्रॉनिक फार्म में अपलोड वेबसाइट पर 100% तक संपीकृत होना चाहिए। प्रस्ताव प्रस्तुत करने की तिथि के साथ प्रस्ताव डिजिटल साईन के साथ नहीं होगा। उक्त प्रस्ताव को प्रस्ताव नहीं माना जाएगा। कोई भी प्रस्ताव जर्नेल भौतिक फार्म में स्वीकार्य नहीं होगा।
- (द) ऑन लाइन भिविदा निर्धारण दिनांक एवं समय के अनुसार खोली जाएगी।
- (ध) ऑन लाइन भिविदा प्रणाली को खोलने से पूर्व भिविदादाताओं को सुनिश्चित कर लें कि प्रणाली से सम्बन्धित सभी आवश्यक दस्तावेजों को स्कैन करके भिविदा प्रणाली को सफलतापूर्वक अपलोड कर दी जाएगी।
- (र) ऑन लाइन भिविदा प्रणाली में किसी कारण से लैट हो जाता है तो उसका सम्बन्धित प्रभाग को सूचित करके प्रणाली से सम्बन्धित सभी सूचियों को सम्पूर्ण रूप से भरकर ऑन लाइन दर्ज करें।
- (ल) ऑन लाइन भिविदा में सभी सारे गये दस्तावेज को ई-भिविदा पोर्टल पर अपलोड करना होगा।

(डॉ. टी शुभमंगला)

I.A.S.

आयुक्त

नगर निगम, (दक्षिण) जोधपुर

दिनांक :- 05/07/2024

क्रमांक. स / एफ 15 / कार्य / 2024 / RL-13942 to 13946  
पतिलिपि:

- निर्देशक स्थानिय निकाय जोधपुर।
- उप निर्देशक स्थानिय निकाय जोधपुर।
- वरिष्ठ लेखाधिकारी नगर निगम दक्षिण जोधपुर।
- नोटिस क्लर्क नगर निगम दक्षिण जोधपुर।
- औसवाल डाटा प्रोसेस नगर निगम जोधपुर, इस भिविदा को निगम वेब साईट पर अपलोड करावे।

आयुक्त

नगर निगम, (दक्षिण) जोधपुर

RajKaj Ref  
8695130

Signature valid

Digitally signed by T  
Shubhamangala  
Designation : Commissioner  
Date: 2024.07.05 16:17:54 IST  
Reason: Approved

Scanned by CamScanner

Scanned with CamScanner

# Jodhpur Municipal Corporation (South), Jodhpur

①


Name of work:-  
RUIDP-2023

**Supply and stringing of road light phase wire in ward no 78 TO 80 JMC South zone.**

		Schedule	("G" Schedule)		
Sn.	CODEno	PARTICULARS	QTY.	RATE	AMOUNT
1	68.24	Supplying and drawing of XLPE insulated LT Aerial bunched Aluminium conductor cable confirming to IS 14255/1995 and IS 398 (Pt-4)/ 1994 and as per Discom Specs. on existing cross arms through I hook with all necessary T&P required including iniding and twisting etc. complete in all respect as required. All as per pre approved by Engineer in-charge. For additional technical parameters of products/ work , refer Annexure "A" attached with this BSR .			
	68.24.2	1 X 25 sq. mm. + 1X25 sq. mm. (insulated)	7300	Mtr	65.00
				Each	474500
2	68.3	Supply and fixing of following LT Supporting accessories with nut bolt & Clamps made out as per standard Discom's specifications with two coats of Red oxide and two coats of Aluminium paint etc. as required. All as per pre approved by Engineer in-charge. For additional technical parameters of product / work refer Annexure 'A' attached with this BSR			
	68.3.1	LT cross arm 600 mm long with clamp	450	Nos	472.00
				Each	212400
3	68.4	Supply and fixing of LT porcelain pin insulator as per IS 1445-1997 and as per Discom's standard specifications, suitable for working voltage 1100 volts including all accessories like MS Forged GI LT Pin confirming to IS:7935/1975 (latest amended) Nut, Bolt etc. as required. All as per pre approved by Engineer in-charge. For additional technical parameters of product / work refer Annexure 'A' attached with this BSR			
	68.4.1	100 mm x 70 mm	450	Nos	110.00
				Each	49500
4	68.5	Supply and fixing of LT porcelain shackle insulator as per IS:1443 1979 and as per Discom's standard specifications, suitable for working voltage 1100 volts including all accessories like GI Hardware fittings confirming to IS:7935/1975 (latest amended) Nut, Bolt etc. as required. All as per pre approved by Engineer in-charge. For additional technical parameters of product / work refer Annexure 'A' attached with this BSR			
	68.5.1	75mm x 90mm	120		112.00
				Each	13440
<b>TOTAL G Schedule</b>					<b>749840.00</b>

XEN(Elect)

I agree to do above "G" Schedule work @ .....above/below on RUIDP 2023 electric with JMC terms and conditions..

  
 Signature of Contractor

# Jodhpur Municipal Corporation (South), Jodhpur

2

Name of work:-  
RUIDP-2023

Supply and stringing of road light phase wire in ward no. ( 38 to 77 ) JMC South zone.

		Schedule	("G" Schedule)			
Sn.	CODEno	PARTICULARS	QTY.		RATE	AMOUNT
1	68.24	Supplying and drawing of XLPE insulated LT Aerial bunched Aluminium conductor cable confirming to IS 14255/1995 and IS 398 (Pt-4)/ 1994 and as per Discom Specs. on existing cross arms through I hook with all necessary T&P required including binding and twisting etc. complete in all respect as required. All as per pre approved by Engineer in-charge. For additional technical parameters of products/ work , refer Annexure "A" attached with this BSR .				
	68.24.2	1 X 25 sq. mm. + 1X25 sq. mm. (insulated)	7000	Mtr	65.00	Each 455000
2	68.3	Supply and fixing of following LT Supporting accessories with nut bolt & Clamps made out as per standard Discom's specifications with two coats of Red oxide and two coats of Aluminium paint etc. as required. All as per pre approved by Engineer in-charge. For additional technical parameters of product / work refer Annexure 'A' attached with this BSR				
	68.3.1	LT cross arm 600 mm long with clamp	400	Nos	472.00	Each 188800
3	68.4	Supply and fixing of LT porcelain pin insulator as per IS 1445-1997 and as per Discom's standard specifications. suitable for working voltage 1100 volts including all accessories like MS Forged GI LT Pin confirming to IS:7935/1975 (latest amended) Nut. Bolt etc. as required. All as per pre approved by Engineer in-charge. For additional technical parameters of product / work refer Annexure 'A' attached with this BSR				
	68.4.1	100 mm x 70 mm	400	Nos	110.00	Each 44000
4	68.5	Supply and fixing of LT porcelain shackle insulator as per IS:1443 1979 and as per Discom's standard specifications. suitable for working voltage 1100 volts including all accessories like GI Hardware fittings confirming to IS:7935/1975 (latest amended) Nut. Bolt etc. as required. All as per pre approved by Engineer in-charge. For additional technical parameters of product / work refer Annexure 'A' attached with this BSR				
	68.5.1	75mm x 90mm	100	Nos	112.00	Each 11200
<b>TOTAL G Schedule</b>						<b>699000.00</b>
say						<b>7.00 lac</b>

*(Signature)*  
**XEN(Elect)**  
JMC

I agree to do above "G" Schedule work @ .....above/below on RUIDP 2023 electric with JMC terms and conditions..

Signature of Contractor

Electrification work from sardarpura Thana to Children park in jmc south, Zone(2) Jodhpur.

Sl. No.	CODE No.	Schedule PARTICULARS	("G" Schedule)			AMOUNT	
			QTY.	UNIT	RATE		
1	67.1	Supply and erection of Galvanized iron pole with galvanizing done in single dipping (Average coating thickness Minimum 65 Microns) continuously tapered poles having Octagonal / Circular cross-sections designed to withstand the maximum wind speed as per IS 875. The pole shaft shall be made from sheet steel (HT Steel conforming to grade S355JO) and conforming to IS:R 10025 and shall be continuously tapered with single longitudinal welding. There shall not be any circumferential welding. The welding of pole shaft shall be done by Submerged Arc Welding (SAW) process. pole shafts shall be provided with the rigid flange plate of suitable thickness (Fe 410 conforming to IS 226 / IS 2062) with provision for fixing 4 no. foundation bolts. This base plate shall be fillet welded to the pole shaft at two locations i.e. from inside and outside. The octagonal Poles shall have lockable disc of approximate 500 mm length at the elevation of 500 mm from the Base plate with bakelite sheet having 6 SP MCB and 16 spm stud type connector (4 nos) inside the pole at disc opening for cable connection of following length and dimension as per table P-01 with base plate and foundation bolt on the existing cement concrete foundation All as per pre approved by Engineer in-charge. For additional technical parameters of products/work, refer Annexure "A" attached with this BSR.					
	67.1.1	Poles with Octagonal Cross Section (8 Mtr)	20	Nos	15520	Each	310400
2	67.2	Supply and Fixing of Pole O/M fabricated hot dipped galvanized MS Overhang (48.3 X 3.25 mm) with cap (400 X 88.9 / 114.3 X 3.25 mm) over the existing poles. All as per pre approved by Engineer in-charge. For additional technical parameters of products/work, refer Annexure "A" attached with this BSR.					
	67.2.2	Double arm overhang	20	Nos	3397.00	Each	67940
3	67.12	Providing & Fixing of IK08, IP 66 protected LED Street Light Luminaire on existing bracket/pole. Fixture made of powder coated single piece pressure cast aluminum material with heat dissipation fins on housing with UV stabilized PC (UV stabilization report submitted for UV cover) / Toughened Glass cover and secondary lens on each LED & should be SMD type of 3 to 5 watt each. The System efficiency >=125 lm/wt and potted driver & has a unique BSR number with Input Voltage AC 120 to 270 V AC with High voltage CutOff (V>=300 V AC and Auto resetting Safety, Power Factor >=0.95 driver Efficiency >=85%, THDI <10%, Humidity 10% to 90%, RH Working Temp -5C to 45C, driver current <=750mA. The luminaire shall be BSR certified and Trade mark certified. Life Expectancy Equal or more than 50000 burning hrs with Minimum 70% lumen maintained. CRI >=70 and CCT 5700K +355K. Surge protection shall be min >= 4 KV internal and min 10 KV external inside driver compartment. driver should be Phase to phase protection of 440 V for 4 Hrs. Manufactures Word Mark/Name Engraved/Embossing on die cast housing to allow traceability/authenticity. Fixture shall be AS PER IS 10322 Compliant OEM Must have its own in house NABL lab setup for all testing facilities for LED fixtures. (LM79LM80) Certificate/report with liable warranty of product/accessories from OEM shall be submitted. All as per pre approved by Engineer in-charge. For additional technical parameters of products/work, refer Annexure "A" attached with this BSR.					
	67.12.5	LED Street Light fixture with Minimum lumen output 8700 lm	40	Nos	5993.00	Each	239720
4	67.11	Providing & Fixing of IK08 IP 66 protected high power LED flood light system with single piece Pressure diecast aluminum housing, toughened glass diffuser with suitable lenses on LED to achieve various beam angles, of high power LED of 3 to 5 watt each. Integrated potted driver as a unique BSR number having efficiency more than 85% and in compliance to BSR certified and Trade mark certificate. The System level luminaire efficacy >=125 lm/wt LED driver Input Voltage AC 120 to 270 V AC with High voltage CutOff (V>=300 V AC and Auto resetting Safety, Power Factor >=0.95, THDI <10%, driver current <=750mA, driver should be Phase to phase protection of 440 V for 4 Hrs. Electrical Connector, Surge Protection Min >=4KV internal and 10KV external but inside driver compartment. System life of 50000 Burning hours with 70% of Initial Lumens maintained, CRI >=70 and CCT 5700K +355K. Manufactures Word Mark/Name Engraved/Embossing/Screen printing on die cast housing to allow traceability/authenticity. Fixture shall be IS 10322 Compliant OEM Must have its own in house NABL lab setup for all testing facilities for LED fixtures. (LM79LM80) Certificate/report with liable warranty of product/accessories from OEM shall be submitted. All as per pre approved by Engineer in-charge. For additional technical parameters of products/work, refer Annexure "A" attached with this BSR.					
		High Power LED Flood Light Minimum lumen output 12400 lm	4	Nos	6048.00	Each	24192
5	53.1	Supplying and drawing ER PVC insulated & unsheathed flexible copper conductor as per PWD specification for electrical Works with ISI marked (IS 694) and as per IS 8130 - 2013 of 1.1 KV grade. Wire should be made from 99.99% purity copper, class 3 stranding in accordance to IS 8130/IEC 60228 for lower watt loss, oxygen free for less chances of oxidation, insulation PVC type A/C/D, flame retardant as per IS 10810-53, better ampere rating as per IS 3961 part 3, in existing surface or recessed PVC/MS conduit/casing capping making connections with Copper Lugs of suitable size, Ferrules/testing etc. as required. OEM Must have its own in house NABL lab setup for all testing facilities for wires. For additional technical parameters of product /work refer Annexure "A" attached with this BSR.					
	53.1.2	2 X 1.5 sqmm	500	Mtr	44.00	RM	22000
6	60.2	Providing & Laying P.V.C / XLPE insulated & P.V.C sheathed Armoured Aluminum cable conforming to IS 1554 (1-1/IS 7098 P-1 of 1.1 KV with H4- Grade electrolytic aluminum conductor conforming to IS 8130 of purity >=99.6%, round / flat strip armoring of cables. Inner / outer sheath conforming to IS 5831 in existing RCC / Duct / Stone/ware / PVC pipe/ open duct/cable trench / Cable tray (with cable tie) including testing etc. as required of following size. OEM must have its own in house NABL accredited laboratory for testing procedure as per IS 10810 For additional technical parameters of product /work refer Annexure "A" attached with this BSR.					
	60.2.3	100 Sqmm	700	Mtr	197.00	RM	137900
	60.2.3.3	4 core					
	60.2.2	600 sqmm	200	Mtr	131.00	RM	26200
	60.2.2.1	2 core					
7	50.4	S&E following sizes (dia) of ISI marked virgin material MBMS (IS 9537 P - III ) PVC conduit along with ISI marked (IS 3419-1988) accessories as required in recess including cutting the wall covering conduit and making good the same as required. For additional technical parameters of product /work refer Annexure "A" attached with this BSR.					
	50.4.4	40 mm	700	Mtr	118.00		82600
8	67.8	Providing and Laying RCC Foundation for Octagonal / Conical Street Light poles. High mast Poles as per Drawing attach at Table P-4 with Following Procedure & All as per pre approved by Engineer in-charge. For additional technical parameters of products/work, refer Annexure "A" attached with this BSR. A) Excavation of Pit for Foundation Size upto required depth from Ground level B) Dressing of Pit and Dry stone piling 200 mm thick including supply of stones and preparing surface complete C) Providing and laying in position cement concrete of M-10 grade of 75 mm thickness D) Reinforcement for RCC work with TMT bars including straightening, cutting, bending, placing in position and binding all complete E) Centring and shuttering including strutting, propping etc. and removal of form work for Footing and Pedestal F) Providing & Fixing of 2 no. Required Size PTH/HDPE Pipe & Foundation Bolt with template as per O/M Recommendations G) Providing and Laying Reinforcement concrete of M-25 grade in Footing and Pedestal including curing the foundation for 7 days H) Providing and Fixing Nosing Angle 40 mm x 40 mm x 6mm with 2 no. 100 mm long, 10 mm dia. Lugs on each face.					
	67.8.2	Pole Foundation for Octagonal pole from 7 Mtr. To 9 Mtr.	20	Nos	8142.00	Each	162840
<b>TOTAL G Schedule</b>							1073792.00
<b>Say</b>							10.74 Lacs

*Handwritten signature*  
M. S. K. S.

I agree to do above "G" Schedule work as above/below on RUJDP 2023 electric with IMC terms and conditions

Signature of Contractor



Jodhpur Municipal Corporation (South), Jodhpur

4

of Supplying and fixing of SIM in ward 38 to 80 in Jodhpur (south)  
 Date: DP-2023

Sl. No.	CODE No	PARTICULARS	("G" Schedule)			AMOUNT	
			QTY.	RATE			
1	67.1	Supply and erection of Galvanized Iron pole with galvanizing done in single dipping (Average coating thickness Minimum 65 Microns) continuously tapered poles having Octagonal / Circular cross-sections designed to withstand the maximum wind speed as per IS 875. The pole shaft shall be made from sheet steel (HT Steel conforming to grade S355JO) and conforming to BSEN 10025 and shall be continuously tapered with single longitudinal welding. There shall not be any circumferential welding. The welding of pole shaft shall be done by Submerged Arc Welding (SAW) process. Pole shafts shall be provided with the rigid flange plate of suitable thickness (Fe 410 conforming to IS 226 / IS 2062) with provision for fixing 4 no. foundation bolts. This base plate shall be fillet welded to the pole shaft at two locations i.e. from inside and outside. The octagonal Poles shall have lockable door of approximate 500 mm length at the elevation of 500 mm from the Base plate with bakelite sheet having 6A SP MCB and 16 sqmm stud type connector (4 nos) inside the pole at door opening for cable connection of following length and dimension as per table P-01 with base plate and foundation bolt on the Existing cement concrete foundation All as per pre approved by Engineer in-charge. For additional technical parameters of products/ work, refer Annexure "A" attached with this BSR.					
	67.1.1.6	Poles with Octagonal Cross Section (8 Mtr.)	12	Nos	15520	Each	186240
2	67.2	Supply and Fixing of Pole OEM fabricated hot dipped galvanised MS Overhang (48.3 X 3.25 mm) with cap (400 x 88.9 / 114.3 x 3.25 mm) over the existing poles. All as per pre approved by Engineer in-charge. For additional technical parameters of products/ work, refer Annexure "A" attached with this BSR.					
	67.2.2	Double arm overhang	24	Nos	3397.00	Each	81528
3	67.11	Providing & Fixing of IK08 IP-66 protected high power LED flood light system with single piece Pressure diecast aluminum housing, toughened glass diffuser with suitable lenses on LED to achieve various beam angles, of high power LED of 3 to 5 watt each. Integrated potted driver as a unique BIS R number having efficiency more than 85% and in compliance to BIS certified and Trade mark certificate. The System level Luminaire efficacy >=125 lm/wt. LED driver Input Voltage AC 120 to 270 V AC with High voltage Cutoff a >=200 V AC and Auto resetting Safety. Power Factor >0.95, THDI <10%, driver current <=750mA, driver should be Phase to phase protection of 440 V for 4 Hrs. Electrical Connector, Surge Protection Min >=4KV internal and 10KV external but inside driver compartment. System life of 50000 Burning hours with 70% of Initial Lumens maintained. CRI>70 and CCT 5700K ±355K, Manufactures Word Mark/Name Engraved/Embossing/Screen printing on die cast housing to allow traceability/authenticity. Fixture shall be IS 10322 Compliant OEM Must have its own in house NABL lab setup for all testing facilities for LED fixtures (LM79/LM80) Certificate/ report with liable warranty of product/accessories from OEM shall be submitted. All as per pre approved by Engineer in-charge. For additional technical parameters of products/ work, refer Annexure "A" attached with this BSR.					
	67.11.5	High Power LED Flood Light Minimum lumen output 12400 lm	48	Nos	6048.00	Each	290204
4	60.2	Providing & Laying P.V.C. / XLPE insulated & P.V.C. sheathed Armoured Aluminium cable conforming to IS 1554 P-I / IS :7098 P - I of 1.1 KV with H4- Grade electrolytic aluminum conductor conforming to IS 8130 of purity >99.6%, round / flat strip armouring of cables, inner / outer sheath conforming to IS:5831 in existing RCC / Hume / Stoneware / PVC pipe/ open duct/cable trench / Cable tray (with cable tie) including testing etc. as required of following size. OEM must have it's own in house NABL accredited Laboratory for testing procedure as per IS:10810. For additional technical parameters of product / work refer Annexure 'A' attached with this BSR.					
	60.2.3	10.0 Sq mm	400	Mtr.	197.00	RM	78800
	60.2.3.3	4 core	300	Mtr.	131.00	RM	39300
	60.2.2	6.0 sq mm					
	60.2.2.1	2 core					
5	53.1	Supplying and drawing FR PVC insulated & unsheathed flexible copper conductor as per PWD specification for electrical Works with ISI marked (IS 694) and as per IS 8130 : 2013 of 1.1 kv grade. Wire should be made from 99.90% purity copper, class 5 stranding in acc. to IS:8130/IEC 60228 for lower watt loss, oxygen free for less chances of oxidation, insulation PVC type A/C/D, flame retardant as per IS 10810-53, better ampere rating as per IS 3961 part 5, in existing surface or recessed PVC/ MS conduit/casing capping making connections with Copper Lugs of suitable size, Ferrules, testing etc. as required. OEM Must have its own in house NABL lab setup for all testing facilities for wires. For additional technical parameters of product / work refer Annexure 'A' attached with this BSR.					
	53.1.2	2 x 1.5 sq mm	480		44.00		21120
6	50.4	S&F following sizes (dia.) of ISI marked virgin material MMS ( IS:9537 P - III ) PVC conduit along with ISI marked (IS:3419-1988) accessories as required in recess including cutting the wall, covering conduit and making good the same as required. For additional technical parameters of product / work refer Annexure 'A' attached with this BSR.					
	50.4.4	40 mm	400	Mtr.	118.00		47200
7	67.8	Providing and Laying RCC Foundation for Octagonal / Conical Street Light poles. High mast Poles as per Drawing attach at Table P-4 with Following Procedure & All as per pre approved by Engineer in-charge. For additional technical parameters of products/ work, refer Annexure "A" attached with this BSR. A) Excavation of Pit for Foundation Size upto required depth from Ground level B) Dressing of Pit and Dry stone pitching 200 mm thick, including supply of stones and preparing surface complete. C) Providing and laying in position cement concrete of M-10 grade of 75 mm thickness D) Reinforcement for RCC work with TMT bars including straightening, cutting, bending, placing in position and binding all complete. E) Centring and shuttering including strutting, propping etc. and removal of form work for Footing and Pedestal F) Providing & Fixing of 2 no. Required Size PLB HDPE Pipe & Foundation Bolt with template as per OEM Recommendations G) Providing and Laying Reinforce cement Concrete of M-25 grade in Footing and Pedestal including Curing the foundation for 7 days H) Providing and Fixing Nosing Angle 40 mm x 40 mm x 6mm with 2 no. 100 mm long.					
	67.8.2	Pole Foundation for Octagonal pole from 7 Mtr. To 9 Mtr.	12	Nos	8142.00	Each	97704
TOTAL G Schedule							842196.00

*[Signature]*  
 XEN(Llect)

I agree to do above "G" Schedule work at above/below on RUIDP 2023 electric with JMC terms and conditions.

Signature of Contractor

# Jodhpur Municipal Corporation (South), Jodhpur

5

Name of **Supplying and fixing of LED's in ward 38 to 80 in MCJ south**,  
RUIDP-2023

		Schedule	("G" Schedule)				
Sn.	CODEno	PARTICULARS	QTY.		RATE	AMOUNT	
1	67.12	Providing & Fixing of IK08, IP 66 protected LED Street Light Luminaire on existing bracket pole. Fixture made of powder coated single piece pressure die cast aluminum material with heat dissipation fins on housing with UV stabilized PC (UV stablization report submitted for UV cover ) /Toughened Glass cover and secondary lens on each LED & should be SMD type of 3 to 5 watt each The System efficacy =125 lm /w and potted driver & has a unique BIS R number with Input Voltage AC 120 to 270 V AC with High voltage Cutoff @>=300 V AC and Auto resetting Safety . Power Factor >0.95 driver Efficiency >85% ,THD(I) <10% Humidity 10% to 90% RH Working Temp -5C to 45C . driver current <750mA. The luminaire shall be BIS certified and Trade mark certified. Life Expectancy Equal or more than 50000 burning hrs with Minimum 70% lumen maintained . CRI >70 and CCT 5700K +355K. Surge protection shall be min ≥ 4 KV internal and min 10 KV external inside driver compartment driver should be Phase to phase protection of 440 V for 4 Hrs Manufactures Word Mark Name Engraved/Embossing on die cast housing to allow traceability/authenticity. Fixture shall be AS PER IS 10322 Complianced.OEM Must have its own in house NABL lab setup for all testing facilities for LED fixtures. (LM79 LM80) Certificate/ report with liable warranty of product/accessories from OEM shall be submitted. All as per pre approved by Engineer in-charge. For additional technical parameters of products/ work , refer Annexure "A" attached with this BSR .					
	67.12.4	LED Street Light fixture with Minimum lumen output 5600 lm	250	Nos	4249.00	Each	1062250.00
	67.12.5	LED Street Light fixture with Minimum lumen output 8700 lm	250	Nos	5893.00	Each	1482250.00
2	67.18	Providing & Fixing of Street light bracket made out from following size of 'B' class . Medium class G.I. Pipe conforming to IS : 1239 P - 1 ( 2004 ) with heavy duty pole clamp, Saddles suitable fastners etc. as required. All as per pre approved by Engineer in-charge. For additional technical parameters of products/ work , refer Annexure "A" attached with this BSR .					
		32 mm Dia	500	Mtr	761.00	RM	380500.00
3	53.1	Supplying and drawing FR PVC insulated & unsheathed flexible copper conductor as per PWD specification for electrical Works with ISI marked (IS-694) and as per IS 8130 : 2013 of 1.1 kV grade . Wire should be made from 99.90 % purity copper. class 5 stranding in acc. to IS:8130 IEC 60228 for lower watt loss . oxygen free for less chances of oxidization, insulation PVC type A/C/D . flame retardant as per IS 10810-53, better amperage rating as per IS:3961 part 5, in existing surface or recessed PVC/ MS conduit/casing capping making connections with Copper Lugs of suitable size, Ferrules,testing etc. as required. OEM Must have its own in house NABL lab setup for all testing facilities for wires. For additional technical parameters of product / work refer Annexure 'A' attached with this BSR					
	53.1.2	2 x 1.5 sq.mm	2000	Mtr.	44.00	RM	88000.00
<b>TOTAL G Schedule</b>							<b>3029000.00</b>

*XEN*  
XEN(Elect)

I agree to do above "G" Schedule work @ .....above/below on RUIDP 2023 electric with JMC terms and conditions..

Signature of Contractor

Jodhpur Municipal Corporation (South), Jodhpur

Name of work:- RUIDP-2023

Supplying and fixing of LED's in ward 80 in MCJ south

Sl. No.	CODE No	Schedule PARTICULARS	("G" Schedule)				
			QTY.	RATE	AMOUNT		
1	67.12	Providing & Fixing of IK08, IP 66 protected LED Street Light Luminaire on existing bracket pole. Fixture made of powder coated single piece pressure die cast aluminum material with heat dissipation fins on housing with UV stabilized PC (UV stablization report submitted for UV cover ) /Toughened Glass cover and secondary lens on each LED & should be SMD type of 3 to 5 watt each . The System efficacy >=125 lm/ wt and potted driver & has a unique BIS R number with Input Voltage AC 120 to 270 V AC with High voltage Cutoff @>=300 V AC and Auto resetting Safety , Power Factor >0.95 driver Efficiency >85% ,THD(I) <10% Humidity 10% to 90% RH Working Temp -5C to 45C . driver current <750mA. The luminaire shall be BIS certified and Trade mark certified. Life Expectancy Equal or more than 50000 burning hrs with Minimum 70% lumen maintained , CRI >70 and CCT 5700K +355K. Surge protection shall be min ≥ 4 KV internal and min 10 KV external inside driver compartment driver should be Phase to phase protection of 440 V for 4 Hrs. Manufactures Word Mark/Name Engraved/Embossing on die cast housing to allow traceability/authenticity. Fixture shall be AS PER IS 10322 Complianced.OEM Must have its own in house NABL lab setup for all testing facilities for LED fixtures. (LM79/LM80) Certificate/ report with liable warranty of product/accessories from OEM shall be submitted. All as per pre approved by Engineer in-charge. For additional technical parameters of products/ work , refer Annexure "A" attached with this BSR .					
	67.12.4	LED Street Light fixture with Minimum lumen output 5600 lm	115	Nos	4249.00	Each	488635.00
2	67.18	Providing & Fixing of Street light bracket made out from following size of 'B' class . Medium class G.I. Pipe conforming to IS : 1239 P - 1 ( 2004 ) with heavy duty pole clamp, Saddles suitable fastners etc. as required. All as per pre approved by Engineer in-charge. For additional technical parameters of products/ work , refer Annexure "A" attached with this BSR .					
	67.18.3	32 mm Dia	115	Mtr	761.00	RM	87515.00
3	53.1	Supplying and drawing FR PVC insulated & unsheathed flexible copper conductor as per PWD specification for electrical Works with ISI marked (IS-694) and as per IS 8130 : 2013 of 1.1 kV grade . Wire should be made from 99.90 % purity copper, class 5 stranding in acc. to IS:8130 IEC 60228 for lower watt loss , oxygen free for less chances of oxidization. insulation PVC type A/C/D , flame retardant as per IS 10810-53, better amperage rating as per IS 3961 part 5, in existing surface or recessed PVC/ MS conduit/casing capping making connections with Copper Lugs of suitable size, Ferrules,testing etc. as required. OEM Must have its own in house NABL lab setup for all testing facilities for wires. For additional technical parameters of product / work refer Annexure 'A' attached with this BSR					
	53.1.2	2 x 1.5 sq.mm	500	Mtr.	44.00	RM	22000.00
<b>TOTAL G Schedule</b>							<b>598150.00</b>

*[Signature]*  
XEN(Elect)  
JMC

I agree to do above "G" Schedule work @ .....above/below on RUIDP 2023 electric with JMC terms and conditions


Signature of Contractor

Jodhpur Municipal Corporation (South), Jodhpur

Name of work:-  
RUIDP-2023

Supplying and fixing of LED's in ward 78 in MCJ south

Sn.	CODE no	Schedule PARTICULARS	("G" Schedule)			
			QTY.		RATE	AMOUNT
1	67.12	Providing & Fixing of IK08, IP 66 protected LED Street Light Luminaire on existing bracket/pole. Fixture made of powder coated single piece pressure die cast aluminum material with heat dissipation fins on housing with UV stabilized PC (UV stabilization report submitted for UV cover) /Toughened Glass cover and secondary lens on each LED & should be SMD type of 3 to 5 watt each. The System efficacy >=125 lm/ wt and potted driver & has a unique BIS R number with Input Voltage AC 120 to 270 V AC with High voltage Cutoff @>=300 V AC and Auto resetting Safety, Power Factor >0.95 driver Efficiency >85%, THD(I) <10% Humidity 10% to 90% RH Working Temp -5C to 45C, driver current <750mA. The luminaire shall be BIS certified and Trade mark certified. Life Expectancy Equal or more than 50000 burning hrs with Minimum 70% lumen maintained, CRI >70 and CCT 5700K +355K. Surge protection shall be min >= 4 KV internal and min 10 KV external inside driver compartment. driver should be Phase to phase protection of 440 V for 4 Hrs. Manufactures Word Mark Name Engraved/Embossing on die cast housing to allow traceability/authenticity. Fixture shall be AS PER IS 10322 Complianced OEM Must have its own in house NABL lab setup for all testing facilities for LED fixtures. (LM79/LM80) Certificate/ report with liable warranty of product/accessories from OEM shall be submitted. All as per pre approved by Engineer in-charge. For additional technical parameters of products/ work, refer Annexure "A" attached with this BSR.				
	67.12.4	LED Street Light fixture with Minimum lumen output 5600 lm	175	Nos	4249.00	743575.00
	67.12.5	LED Street Light fixture with Minimum lumen output 8700 lm	50	Nos	5993.00	299650.00
2	67.18	Providing & Fixing of Street light bracket made out from following size of 'B' class, Medium class G.I. Pipe conforming to IS : 1239 P - 1 ( 2004 ) with heavy duty pole clamp, Saddles suitable fastners etc. as required. All as per pre approved by Engineer in-charge. For additional technical parameters of products/ work, refer Annexure "A" attached with this BSR.				
	67.18.3	32 mm Dia	220	Mtr	761.00	167420.00
3	53.1	Supplying and drawing FR PVC insulated & unsheathed flexible copper conductor as per PWD specification for electrical Works with ISI marked (IS:694) and as per IS 8130 : 2013 of 1.1 kV grade. Wire should be made from 99.90 % purity copper, class 5 stranding in acc. to IS:8130/IEC 60228 for lower watt loss, oxygen free for less chances of oxidization, insulation PVC type A/C/D, flame retardant as per IS 10810-53, better amperage rating as per IS:3961 part 5, in existing surface or recessed PVC/ MS conduit/casing capping making connections with Copper Lugs of suitable size, Ferrules,testing etc. as required. OEM Must have its own in house NABL lab setup for all testing facilities for wires. For additional technical parameters of product / work refer Annexure 'A' attached with this BSR				
	53.1.2	2 x 1.5 sq.mm	650	Mtr	44.00	28600.00
<b>TOTAL G Schedule</b>						<b>1239245.00</b>

  
XEN(Elect)  
JMC

I agree to do above "G" Schedule work @ .....above/below on RUIDP 2023 electric with JMC terms and conditions.

Signature of Contractor

Jodhpur Municipal Corporation (South), Jodhpur

Name of work:-

Supply and fixing of LED street light in ward 1 to 37 in MCJS.

RUIDP-2023

Sn.	CODEno	Schedule PARTICULARS	("G" Schedule)				AMOUNT
			QTY.		RATE		
1	67.12	Providing & Fixing of IK08, IP 66 protected LED Street Light Luminaire on existing bracket/pole. Fixture made of powder coated single piece pressure die cast aluminum material with heat dissipation fins on housing with UV stabilized PC (UV stablization report submitted for UV cover ) /Toughened Glass cover and secondary lens on each LED & should be SMD type of 3 to 5 watt each . The System efficacy >=125 lm/ wt and potted driver & has a unique BIS R number with Input Voltage AC 120 to 270 V AC with High voltage Cutoff @>=300 V AC and Auto resetting Safety , Power Factor >0.95 driver Efficiency >85% ,THD(I) <10% Humidity 10% to 90% RH Working Temp -5C to 45C . driver current <750mA. The luminaire shall be BIS certified and Trade mark certified. Life Expectancy Equal or more than 50000 burning hrs with Minimum 70% lumen maintained , CRI >70 and CCT 5700K +355K. Surge protection shall be min ≥ 4 KV internal and min 10 KV external inside driver compartment. driver should be Phase to phase protection of 440 V for 4 Hrs. Manufactures Word Mark/Name Engraved/Embossing on die cast housing to allow traceability/authenticity. Fixture shall be AS PER IS 10322 Complianced.OEM Must have its own in house NABL lab setup for all testing facilities for LED fixtures. (LM79/LM80) Certificate/ report with liable warranty of product/accessories from OEM shall be submitted. All as per pre approved by Engineer in-charge. For additional technical parameters of products/ work , refer Annexure "A" attached with this BSR .					
	67.12.3	LED Street Light fixture with Minimum lumen output 5600 lm	250	Nos	4,249.00	Each	1062250
	67.12.5	LED Street Light fixture with Minimum lumen output 8700 lm	250	Nos	5,993.00	Each	1498250
2	67.18	Providing & Fixing of Street light bracket made out from following size of ' B ' class , Medium class G.I. Pipe confirming to IS : 1239 P - 1 ( 2004 ) with heavy duty pole clamp, Saddles suitable fastners etc. as required. All as per pre approved by Engineer in-charge. For additional technical parameters of products/ work , refer Annexure "A" attached with this BSR .					
	67.18.3	32 mm Dia.	500	Mtr	761	Each	380500
3	53.1	Supplying and drawing FR PVC insulated & unsheathed flexible copper conductor as per PWD specification for electrical Works with ISI marked (IS:694) and as per IS 8130 : 2013 of 1.1 kV grade . Wire should be made from 99.90 % purity copper, class 5 stranding in acc. to IS:8130/IEC 60228 for lower watt loss , oxygen free for less chances of oxidization, insulation PVC type A/C/D , flame retardant as per IS 10810-53, better amperage rating as per IS:3961 part 5, in existing surface or recessed PVC/ MS conduit/casing capping making connections with Copper Lugs of suitable size, Ferrules,testing etc. as required. OEM Must have its own in house NABL lab setup for all testing facilities for wires. For additional technical parameters of product / work refer Annexure 'A' attached with this BSR					
	53.1.2	2 x 1.5 sq.mm	2000	Mtr	44	Each	88000
<b>TOTAL G Schedule</b>							<b>3029000.00</b>
Sav							<b>3029000.00</b>

*XEN*

XEN(Elect)  
JMC

I agree to do above "G" Schedule work @ ..... above/below on RUIDP 2023 electric with JMC terms and conditions..

Signature of Contractor

निविदादाता द्वारा घोषणा

{सा. नि. एवं लेखा नियम 48 (VII)}

मैं/हम घोषणा करता हूँ/करते हैं कि मैंने/हमने जिन मालों/सामानों/उपकरणों के लिये निविदा दी है, उनका/उनके/मैं/हम थोक विक्रेता/सोल वितरक/प्राधिकृत डीलर/डीलर/सोल विक्रेता/विपणन एजेंट हूँ/हैं।

यदि यह घोषणा असत्य पायी जाये तो किसी भी अन्य कार्यवाही, जो कां. जा सकती है, पर प्रतिकूल प्रभाव डाले बिना, मेरी/हमारी प्रतिभूति को पूर्ण रूप में समपहल कर किया जा सकेगा तथा निविदा को, जिस सीमा तक उसे स्वीकार किया गया है रद्द किया जा सकेगा।

(निविदादाता के हस्ताक्षर)

## Annexure A : Compliance with the Code of Integrity and No Conflict of Interest

Any person participating in a procurement process shall -

- (a) not offer any bribe, reward or gift or any material benefit either directly or indirectly in exchange for an unfair advantage in procurement process or to otherwise influence the procurement process;
- (b) not misrepresent or omit that misleads or attempts to mislead so as to obtain a financial or other benefit or avoid an obligation;
- (c) not indulge in any collusion, Bid rigging or anti-competitive behavior to impair the transparency, fairness and progress of the procurement process;
- (d) not misuse any information shared between the procuring Entity and the Bidders with an intent to gain unfair advantage in the procurement process;
- (e) not indulge in any coercion including impairing or harming or threatening to do the same, directly or indirectly, to any party or to its property to influence the procurement process;
- (f) not obstruct any investigation or audit of a procurement process;
- (g) disclose conflict of interest, if any; and
- (h) disclose any previous transgressions with any Entity in India or any other country during the last three years or any debarment by any other procuring entity.

### Conflict of Interest:-

The Bidder participating in a bidding process must not have a Conflict of Interest.

A Conflict of Interest is considered to be a situation in which a party has interests that could improperly influence that party's performance of official duties or responsibilities, contractual obligations, or compliance with applicable laws and regulations.

- i. A Bidder may be considered to be in Conflict of Interest with one or more parties in a bidding process if, including but not limited to:
  - a. have controlling partners/ shareholders in common; or
  - b. receive or have received any direct or indirect subsidy from any of them; or
  - c. have the same legal representative for purposes of the Bid; or
  - d. have a relationship with each other, directly or through common third parties, that puts them in a position to have access to information about or influence on the Bid of another Bidder, or influence the decisions of the Procuring Entity regarding the bidding process; or
  - e. the Bidder participates in more than one Bid in a bidding process. Participation by a Bidder in more than one Bid will result in the disqualification of all Bids in which the Bidder is involved. However, this does not limit the inclusion of the same subcontractor, not otherwise participating as a Bidder, in more than one Bid; or
  - f. the Bidder or any of its affiliates participated as a consultant in the preparation of the design or technical specifications of the Goods, Works or Services that are the subject of the Bid; or
  - g. Bidder or any of its affiliates has been hired (or is proposed to be hired) by the Procuring Entity as engineer-in-charge/ consultant for the contract.

Doc1

निगमिताता के हस्ताक्षर

## Annexure B : Declaration by the Bidder regarding Qualifications

### Declaration by the Bidder

In relation to my/our Bid submitted to ..... for procurement of ..... in response to their Notice Inviting Bids No..... Dated..... I/we hereby declare under Section 7 of Rajasthan Transparency in Public Procurement Act, 2012, that:

1. I/we possess the necessary professional, technical, financial and managerial resources and competence required by the Bidding Document issued by the Procuring Entity;
2. I/we have fulfilled my/our obligation to pay such of the taxes payable to the Union and the State Government or any local authority as specified in the Bidding Document;
3. I/we are not insolvent, in receivership, bankrupt or being wound up, not have my/our affairs administered by a court or a judicial officer, not have my/our business activities suspended and not the subject of legal proceedings for any of the foregoing reasons;
4. I/we do not have, and our directors and officers not have, been convicted of any criminal offence related to my/our professional conduct or the making of false statements or misrepresentations as to my/our qualifications to enter into a procurement contract within a period of three years preceding the commencement of this procurement process, or not have been otherwise disqualified pursuant to debarment proceedings;
5. I/we do not have a conflict of interest as specified in the Act, Rules and the Bidding Document, which materially affects fair competition;

Date:  
Place:

Signature of bidder  
Name:  
Designation:  
Address:

निविदादाता के हस्ताक्षर

Doc1



Memorandum of Appeal under the Rajasthan Transparency in Public Procurement Act, 2012

Appeal No ..... of .....  
Before the ..... (First / Second Appellate Authority)

1. Particulars of appellant:

(i) Name of the appellant:

(ii) Official address, if any:

(iii) Residential address:

2. Name and address of the respondent(s):

(i)

(ii)

(iii)

3. Number and date of the order appealed against and name and designation of the officer / authority who passed the order (enclose copy), or a statement of a decision, action or omission of the Procuring Entity in contravention to the provisions of the Act by which the appellant is aggrieved:

4. If the Appellant proposes to be represented by a representative, the name and postal address of the representative:

5. Number of affidavits and documents enclosed with the appeal:

6. Grounds of appeal:

.....  
.....  
..... (Supported by an affidavit)

7. Prayer

Place .....

Date .....

Appellant's Signature

निवेदकता के हस्ताक्षर