



जोधपुर नगर निगम, (दक्षिण)



पोलोटैक्निक कॉलेज परिसर, रेजीडेन्सी रोड, जोधपुर

E-Mail- ceo nnl@rediffmail.com, nnlelectrical@gmail.com Tel: 0291.2651464

क्रमांक:- सं./एफ-15/कार्य/2024/RL-14340

दिनांक:- 09/01/2025

ई- निविदा सूचना क्रमांक RL-14340 दिनांक 09/01/2025

UBN No. DLB2425WSOB14742

जोधपुर नगर निगम दक्षिण द्वारा इच्छुक कार्यो के अनुभवी/योग्यताधारी, डिजिटल विद्युत लाईसेन्सधारी संवेदको, नगर निगम में पंजीकृत नियमानुसार E-EWSD श्रेणी संवेदको, अन्य विभाग में पंजीकृत E-EWSD-I ऑन-लाईन "ई" टेण्डर प्रक्रिया से निगम शर्तो के अधीन निविदाये आमंत्रित की जाती है। निविदा के कार्यो, योग्यता, शर्तो की समस्त जानकारी वेबसाईट पर www.eproc.raj.in अथवा www.sppp.raj.nic.in अथवा <https://lsg.rajasthan.gov.in/MCJS> पर देखी जा सकती है।

(डॉ. टी शुभमंगला)

I.A.S

आयुक्त

नगर निगम, (दक्षिण) जोधपुर

क्रमांक:- सं./एफ-15/कार्य/2024/RL-~~14340~~ 14345

दिनांक:- 09/01/2025

प्रतिलिपि

1. राजस्थान संवाद जयपुर को भेज कर लेख है कि आगामी अंक में एक राज्य स्तरीय संस्करण एवं जोधपुर संस्करण में प्रकाशित कर बिल भुगतान हेतु प्रस्तुत करे।
2. बिल लिपिक, नगर निगम, जोधपुर।
3. ओसवाल डाटा जोधपुर। इस निविदा www.sppp.raj.nic.in वेब साईट पर अपलोड करावे।
4. मैसर्स इलीट मंत्रा, JMC वेब साईट पर अपलोड करावे।
5. नोटिस बोर्ड नगर निगम जोधपुर।

आयुक्त

नगर निगम, (दक्षिण) जोधपुर

Document certified by T SHUBHAMANGALA
<shubhamangala.samanvika@gmail.com>

Digitally Signed by T.
SHUBHAMANGALA
Designation: Commissioner
Date: 09-01-2025 11:24:29

पोलोटैक्निक कॉलेज परिसर, रेजीडेन्सी रोड, जोधपुर

E-Mail- ceo nnj@rediffmail.com, nnjelectrical@gmail.com Tel: 0291 2651464

क्रमांक- एफ-15/कार्य/2024/R2-14334

दिनांक- 09/01/2025

ई-निविदा सूचना

UBN No. DLB2425WSOB14742

जोधपुर नगर निगम दक्षिण द्वारा इच्छुक कार्य के अनुमती/योग्यताधारी डिजिटल विद्युत लाईसेन्सधारी संवेदको नगर निगम में पंजीकृत नियमानुसार श्रेणी संवेदको, अन्य विभाग में पंजीकृत EEWSD-I ऑन-लाईन "ई" टेंडर प्रक्रिया में निगम कार्य के अधीन निविदाये आमंत्रित की जाती है। निविदा की शर्त लेखा नियमानुसार रहेगी।

| क्र.सं. | कार्य का नाम | अनुमानित लागत (लाखों में) | अमानत राशि 2% | ई-टेंडर प्रोसेसिंग शुल्क | निविदा प्रपत्र शुल्क | कार्य करने की अवधि |
|---------|--|---------------------------|---------------|--------------------------|----------------------|--------------------|
| 1 | नगर निगम दक्षिण जोधपुर के वार्ड 42 के आदर्श पार्क में नवीनीकरण का कार्य। | 7.95 | 15900 | 500 | 500 | 06 माह |
| 2 | वार्ड सं. 38 से 80 के विभिन्न पार्कों में विद्युत नवीनीकरण का कार्य। | 15.76 | 31520 | 500 | 500 | 01 वर्ष |
| 3 | वार्ड सं. 45 में विभिन्न स्थानों पर एलईडी व सेमीहार्डमास्ट लाइट लगाने का कार्य | 6.34 | 12680 | 500 | 500 | 06 माह |
| 4 | वार्ड सं. 37 में विभिन्न स्थानों पर एलईडी एवं सेमीहार्डमास्ट लगाने का कार्य | 7.00 | 14000 | 500 | 500 | 06 माह |
| 5 | सूरसागर में वार्ड सं. 1 से 37 में विभिन्न स्थानों पर एलईडी लाइट्स लगाने का कार्य | 42.00 | 84000 | 500 | 500 | 06 माह |
| 6 | सूरसागर में वार्ड सं. 1 से 37 में विभिन्न स्थानों पर सोडियम लाइट्स के स्थान पर एलईडी लाइट्स लगाने का कार्य | 42.00 | 84000 | 500 | 500 | 06 माह |

| | |
|---|---|
| निविदा प्रकाशित करने की तिथि | दिनांक 10/01/25 |
| निविदा अपलोड करने की तिथि | दिनांक 10/1/25 से 20/1/25 दिनांक |
| निविदा डाउनलोड/अपलोड करने की अंतिम तिथि व समय | दिनांक 10/1/25 अपराह्न 20/1/25 बजे तक 6:00 pm |
| निविदा के दस्तावेज कार्यालय में जमा कराने की दिनांक | दिनांक 21/1/25 अपराह्न 12:00 बजे तक |
| निविदा खोलने की तिथि व समय | दिनांक 21/1/25 अपराह्न 2:00 बजे तक |

ई-निविदा प्रपत्रों को वेब साईट <http://eproc.rajasthan.gov.in> से अपलोड डाउनलोड किया जा सकता है। इन निविदाओं में भाग लेने वाले संवेदको निविदा को इलेक्ट्रॉनिक फारमेन्ट में वेबसाईट पर <http://eproc.rajasthan.gov.in> जमा कराए। विस्तृत विवरण एवं शर्तों के लिए नगर निगम दक्षिण कार्यालय के विद्युत अनुभाग से जानकारी प्राप्त की जा सकती है।

ई निविदा की महत्वपूर्ण शर्तें निम्नानुसार हैं:-

- आर.टी.पी.पी. एक्ट 2012 एवं आर.टी.पी.पी. रूल्स 2013 के नियम एवं शर्तें निविदा में लागू होंगे।
- निविदा प्रपत्र शुल्क व धरोहर राशि का डिमाण्ड ड्राफ्ट आयुक्त नगर निगम जोधपुर दक्षिण payable जोधपुर होना चाहिए। निविदा जारी के पश्चात् दिनांक की डी.डी. प्रस्तुत करनी होगी अन्यथा निविदा से निरस्त कर दी जायेगी।
- वित्त विभाग के आदेश अनुसार ई-टेंडर प्रोसेसिंग शुल्क 50.00 लाख रुपये तक की राशि के कार्य के लिए 500/- व 50.00 लाख रुपये से अधिक राशि के कार्य के लिए 1500/- रु की राशि निविदा शुल्क के अतिरिक्त देनी होगी जो डिमाण्ड या बैंकर के रूप में देय होगी। यह डिमाण्ड ड्राफ्ट या बैंकर चेक MD, RISL, payable at Jaipur होना चाहिए।
- निविदाकर्ता द्वारा निविदा शुल्क, धरोहर राशि, E-Tender प्रोसेसिंग राशि डिमाण्ड ड्राफ्ट व 100 रुपये का फर्म के ब्लैक लिस्ट नहीं होने का नॉन ज्यूडिशियल स्टॉप की प्रति सम्वन्धित कार्यालय में जमा कराना आवश्यक होगा।
- अमानत राशि/ धरोहर राशि निविदा प्रपत्र में दर्शाई गई कुल अनुमानित लागत की 2% होगी एवं जोधपुर नगर निगम में पंजीकृत संवेदको से 1/2% धरोहर राशि पी डब्ल्यू एफ एण्ड एआर के नियमानुसार देय होगी। इसके अतिरिक्त सभी संवेदको से 2% अमानत राशि देय होगी। नगर निगम में विद्युत पंजीकृत संवेदको को अदेशानुसार पंजीयन रियु कराया जाना आवश्यक होगा, अन्यथा निविदा स्वीकार नहीं की जाएगी। प्रतिभूति घोषणा पत्र की आवश्यकता के लिए निर्धारित समय, दिनांक पर कार्यालय में जमा करानी होगी।
- ई-बोली प्रपत्र दो भागों में है। प्रथम भाग तकनीकी विड है तथा द्वितीय भाग वित्तीय विड है। बोली दाता द्वारा तकनीकी विड हेतु यह प्रपत्र मय संलग्न व बाध्यकारी दस्तावेज के प्रत्येक पृष्ठ पर हस्ताक्षर करते हुये (मय सील) eproc पोर्टल पर अपलोड करनी है। वित्तीय विड ऑनलाईन BOQ में ही प्रस्तुत की जानी है। इससे भिन्न रूप में प्रस्तुत

- प्रस्तावों पर विचार नहीं किया जाएगा। वित्तीय दर वाला बिड ऑन्यूमेन्ट केवल उन्ही फर्मों का खोला जायेगा, जिन्हें कमेटी द्वारा तकनीकी बिड ऑन्यूमेन्ट में योग्य समझा जायेगा।
7. संवेदक को किसी भी राजकीय विभाग अथवा राजकीय उपक्रम में समान प्रकृति के गत 3 वर्षों में निम्नानुसार सम्पादित कार्य जिसका अनुभव/पूर्णता प्रमाण पत्र संलग्न करना आवश्यक होगा—
- एक कार्य का अनुमानित लागत का 80% के बराबर पूर्णता का प्रमाण पत्र संलग्न करना होगा।
 - दो कार्य जिनमें प्रत्येक कार्य का अनुमानित लागत का 50% के बराबर पूर्णता का प्रमाण पत्र संलग्न करना होगा।
 - तीन कार्य जिनमें प्रत्येक कार्य का अनुमानित लागत का 40% के बराबर पूर्णता का प्रमाण पत्र संलग्न करना होगा।
8. संवेदक को किसी भी राजकीय संस्था विभाग, बोर्ड कॉर्पोरेशन अथवा उपक्रम में वर्तमान में ब्लैक-लिस्टेड/डी-अर अथवा डिफाल्टर घोषित नहीं किया होना चाहिए इस संबंध में 100 रुपये के नॉन ज्यूडिशियल स्टाम्प वॉच पर नोटरी से प्रमाणित शपथ-पत्र निविदा के साथ संलग्न किया जाना आवश्यक है।
9. कार्यों के सम्मुख उपरोक्तानुसार वर्णित कार्यालय में संवेदक द्वारा दिनांक 20.11.25 से दिनांक 20.11.25 को वेबसाइट <http://eproc.rajasthan.gov.in> पर देखा जा सकता है, निविदा प्रपत्रों में निविदाकर्ता के लिए योग्यता सूचना तथा निविदाकर्ता की पात्रता, प्लान, स्पेशिफिकेशन उपलब्ध है। सभी दस्तावेजों को निविदा में अपलोड करना होगा।
10. यदि संवेदक का नजदीकी रिश्तेदार (प्रथम रक्त सम्बन्धी व उनके पति/पत्नी) इस कार्य से सम्बन्धित जोधपुर नगर निगम कार्यालय में कार्यरत लेखाकार अथवा तकनीकी स्तर का किसी पद पर पदस्थापित हो तो इस कार्य पर नियुक्ति करने पर प्रतिबन्ध रहेगा।
11. राज्य सरकार में किसी भी अभियांत्रिकी विभाग में किसी भी इंजीनियर अथवा इंजीनियरिंग या प्रशासनिक कार्य पर नियुक्त राजपत्रित अधिकारी राज्य सरकार की अनुमति के बिना सेवा निवृत्ति के 2 वर्ष तक संवेदक अथवा उसके कर्मचारी के रूप में कार्य नहीं कर सकेगा।
12. कार्य पूर्ण करने की अवधि में मानसून अवधि सम्मिलित है।
13. यदि संवेदक द्वारा कार्य पर लगाये जाने वाले श्रमिकों के मध्य कोई विवाद उत्पन्न होता है तो उसकी प्रबंधकीय जिम्मेदारी संवेदक की होगी उसके लिए उपापन संस्था का सक्षम प्राधिकारी न्यूनतम मजदूरी अधिनियम 1948 एवं राजस्थान अनुबंधित श्रमिका (नियमन एवं उन्मुलन) अधिनियम 1970 का पालन करने का उत्तर दायित्व होगा एवं साथ ही संवेदक का पी.एफ. में पंजीकरण अनिवार्य होगा और नवीनतम गरा हुआ पी.एफ. का चालान भी निविदा में अपलोड करना होगा। अन्यथा निविदा निरस्त कर दी जायेगी।
14. फर्म का जीएसटी विभाग द्वारा जारी जीएसटी सर्टिफिकेट नय नवीनतम जीएसटी रिटर्न प्रमाण पत्र की छाया प्रति संलग्न करनी होगी।
15. संवेदक को उपरोक्त कार्य में भाग लेने के लिए विगत तीन वित्तीय वर्षों में निविदा राशि का वार्षिक औसत न्यूनतम 50 प्रतिशत टर्न ओवर प्रतिवर्ष का होना आवश्यक होगा।
16. संवेदक को निविदा में मांगे गये दस्तावेजों की पूर्ति कर लगाया जाना आवश्यक होगा। यदि मांगे गये दस्तावेजों की पूर्ति नहीं किये जाने पर उस फर्म को असफल माना जावेगा।
17. निविदादाता द्वारा दी जाने वाली दरें सही कर सहित होंगी।
18. यदि निविदादाता किसी कार्यादेश की पूर्ति समय पर नहीं कर पावे अथवा आदेशों की अवहेलना करता है, या आदेशों को लेने से मना करता है, तो 5000/- रु. प्रतिदिन की दर से जुर्माना आगामी होने वाले भुगतान राशि में से काटा जावेगा।
19. कार्य की आवश्यकता को देखते हुए दूरभाष पर भी आदेश दिये जा सकेंगे जो ठेकेदार को मान्य होंगे। इसकी पुष्टि के बाद में आदेश जारी किये जा सकेंगे।
20. ठेकेदार के ठेके को निरस्त करने की अवस्था में नगर निगम जोधपुर द्वारा उचित समझे जाने पर निविदा में भाग लेने वाली अन्य फर्मों से प्रथम निविदादाता (वर्तमान ठेकेदार) की अनुमोदित दरों पर कार्य करने की सहमति लेकर कार्य कराया जा सकेगा, जो शोध अवधि के लिए होगा।
21. इस करार के उत्पन्न समस्त विवादों तथा इस करार के निर्वाचन से संबंधित समस्त प्रश्न नगर निगम द्वारा वर्णित किये जायेंगे और नगर निगम जोधपुर का निर्णय अंतिम होगा।
22. प्रिविलेज विवाद की स्थिति में स्थानीय सिविल न्यायालय को ही क्षेत्राधिकार होगा।
23. राज्य सरकार व नगर निगम जोधपुर द्वारा समय समय पर जारी आदेश निर्देश मान्य होंगे।
24. निविदा विफल रहा है के मूल्य की निम्नानुसार प्रतिशत के आधार पर वसूली की जावेगी।
- | | |
|--|---------------|
| • विहित परिदान कालावधि की एक चौथाई कालावधि तक विलम्ब | 2.50 प्रतिशत |
| • विहित कालावधि से एक चौथाई से अधिक किन्तु आधी से अनाधिक कालावधि तक विलम्ब | 5.00 प्रतिशत |
| • विहित कालावधि के आधे से किन्तु तीन चौथाई तक की कालावधि का विलम्ब | 7.50 प्रतिशत |
| • विहित कालावधि के तीन चौथाई से अधिक की कालावधि का विलम्ब | 10.00 प्रतिशत |
| • निर्धारित नुकसान की अधिकतम रकम | 10.00 प्रतिशत |

25. निविदादाता को ई-मेल द्वारा सूचना दी जा सकती है। इसलिए आप अपने वाटसएप नम्बर, ई-मेल तथा मोबाईल नम्बर देने जरूरी होंगे।
26. सतोपलभक कार्य नहीं होने की स्थिति में अनुदाय को किसी भी समय निरस्त किया जा सकता है तथा प्रतिक्रिया राशि लौट कर ली जायेगी।
27. निविदादाता द्वारा किसी भी आईटम की दर प्रस्तुत नहीं करने पर निविदा को अपूर्ण मानकर निरस्त कर दिया जायेगा।
28. यदि किसी निविदादाता द्वारा टेण्डर की राशि से कम दर मरी जाती है तो स्कैन निविदादाता को एक जमा (एन) का पत्र जारी किये जाने के 14 दिवस के अन्दर के अन्दर अन्दर की राशि बीजी/एफडीआर/एनएसटी का कम से कम निगम में जमा करानी होगी। कार्य सतोपलभक पूर्ण होने के परचात वापस लौटा दी जायेगी।
29. निविदादाता द्वारा निविदा प्रपत्र तथा एनेक्सर को स्वयं हस्ताक्षर कर स्कैन करके <http://eproc.rajasthan.gov.in> पर अपलोड करने पर ही निविदा को मान्य किया जायेगा। अन्यथा निविदा निरस्त कर दी जायेगी।
30. निविदादाता दरो की वैधता अवधि खोले जाने की दिनांक से 90 दिवस तक अनुमोदन हेतु मान्य होगी।
31. कार्य की दोष निवारण अवधी 02 वर्ष की रहेगी जिसमें किसी प्रकार की लापरवाही बरतने पर बिल से कटौती मय पेनेल्टी की जाएगी जिसकी समस्त जिम्मेदारी आप स्वयं की रहेगी।
32. सदेवक को RUIDP - 2023 के नियमानुसार Annexure के अनुसार करवाना होगा, जिस पर होने वाला कम सदेवक द्वारा बहन किया जाएगा, निगम द्वारा इस सारथ में कोई भी राशि देय नहीं होगी।
33. ई-टेन्डरिंग के लिए निविदादाता हेतु निर्देश:-
 - (अ) इन निविदाओं में दिलचस्पी लेने वाले निविदादाता निविदा प्रपत्रों का इन्टरनेटसाईट <http://eproc.rajasthan.gov.in> से डाउनलोड कर सकते हैं।
 - (ब) निविदाओं में भाग लेने वाले निविदादाताओं का इन्टरनेट साईट <http://eproc.rajasthan.gov.in> पर रजिस्टर करवाना होगा। ऑन लाईन निविदा में भाग लेने के लिए डिजिटल सर्टिफिकेट इन्फोर्मेशन तकनीक में कम 2000 के तहत प्राप्त करना होगा। जो इलेक्ट्रॉनिक निविदा में साईट करने हेतु काम आयेगा। निविदादाता उपरोक्त डिजिटल सर्टिफिकेट सीसीए द्वारा स्वीकृति एजेन्सी से प्राप्त कर सकते हैं। जिन निविदादाताओं के पास पूर्व में वैध डिजिटल सर्टिफिकेट सीसीए द्वारा स्वीकृति एजेन्सी से प्राप्त कर सकते हैं। जिन निविदादाताओं के पास पूर्व में वैध डिजिटल सर्टिफिकेट है नया डिजिटल सर्टिफिकेट लेने की आवश्यकता नहीं है।
 - (स) निविदादाताओं को निविदा प्रपत्र इलेक्ट्रॉनिक फार्मेट में उपरोक्त वेबसाईट पर डिजिटल सर्टिफिकेट साईन के साथ प्रस्तुत करना होगा, जिसके प्रस्ताव डिजिटल साईन के साथ नहीं होंगे, उनके प्रस्ताव स्वीकार नहीं किये जायेंगे। कोई भी प्रस्ताव अकेले भौतिक फार्म में स्वीकार्य नहीं होगा।
 - (द) ऑन लाईन निविदाएँ निर्धारण दिनांक एवं समय के अनुसार खोली जायेगी।
 - (य) इलेक्ट्रॉनिक निविदा प्रपत्रों को जमा कराने से पूर्व निविदादाताओं यह सुनिश्चित कर लेने को प्रपत्रों से सम्बन्धित सभी आवश्यक दस्तावेज की स्कैन कॉपी निविदा प्रपत्रों के साथ संलग्न कर दी गयी है।
 - (र) कोई भी टेन्डर ऑनलाइन जमा कराने में किसी कारण से लेट हो जाता है तो उसका जिम्मेदार विभाग नहीं होगा।
 - (ल) टेन्डर के प्रपत्रों में आवश्यक सभी सूचियों को सम्पूर्ण रूप से भरकर ऑन लाईन दर्ज करे।
 - (व) ई-निविदा में सभी मांगे गये दस्तावेज को ई-निविदा पोर्टल पर अपलोड करना होगा।

(डॉ. टी शुभमंगला)

I.A.S.

आयुक्त

नगर निगम, (दक्षिण) जोधपुर

दिनांक :- 09/01/2025

क्रमांक:-एफ-15/कार्य/2024/RL-14335 to 14339

प्रतिलिपि:-

- निर्देशक स्थानिय निकाय जयपुर।
- उप- निर्देशक स्थानिय निकाय जोधपुर।
- वरिष्ठ लेखाधिकारी, नगर निगम दक्षिण जोधपुर।
- नोटिस बोर्ड नगर निगम दक्षिण जोधपुर।
- "ओसवाल डाटा प्रोसेस नगर निगम जोधपुर, इस निविदा को निगम वेब साईट पर अपलोड कराते।

आयुक्त

नगर निगम, (दक्षिण) जोधपुर

Document certified by T SHUBHAMANGALA
<shubhamangala.samanvial@gmail.com>.

Digitally Signed by T.
SHUBHAMANGALA
Designation: Commissioner
Date: 09-01-2025 11:24:18

Jodhpur Municipal Corporation (South), Jodhpur

Name of work:-
RUIDP-2023

Renovation of Adarsh park in Ward 42 of nagar nigam south jodhpur.

| S.no. | CODE no | Schedule PARTICULARS | ("G" Schedule) | | | | |
|-------|----------|---|----------------|-----|-----------|--------|--------|
| | | | QTY. | | RATE | AMOUNT | |
| 1 | 67.1 | Supply and erection of Galvanized Iron pole with galvanizing done in single dipping (Average coating thickness Minimum 65 Microns) continuously tapered poles having Octagonal / Circular cross-sections designed to withstand the maximum wind speed as per IS 875, The pole shaft shall be made from sheet steel (HT Steel Conforming to grade S355JO) and conforming to BSEN 10025 and shall be continuously tapered with single longitudinal welding. There shall not be any circumferential welding. The welding of pole shaft shall be done by Submerged Arc Welding (SAW) process. pole shafts shall be provided with the rigid flange plate of suitable thickness (Fe 410 conforming to IS 226 / IS 2062) with provision for fixing 4 no. foundation bolts, This base plate shall be fillet welded to the pole shaft at two locations i.e. from inside and outside. The octagonal Poles shall have lockable door of approximate 500 mm length at the elevation of 500 mm from the Base plate with bakelite sheet having 6A SP MCB and 16 sqmm stud type connector (4 nos) inside the pole at door opening for cable connection of following length and dimension as per table P-01 with base plate and foundation bolt on the Existing cement concrete | | | | | |
| | 67.1.1 | Poles with Octagonal Cross Section | | | | | |
| | 67.1.6 | 8 Mtr. | 16 | Nos | 15,520.00 | Each | 248320 |
| 2 | 67.8 | Providing and Laying RCC Foundation for Octagonal / Conical Street Light poles, High mast Poles as per Drawing attach at Table P-4 with Following Procedure & All as per pre approved by Engineer in-charge. For additional technical parameters of products/ work , refer Annexure "A" attached with this BSR . A) Excavation of Pit for Foundation Size upto required depth from Ground level B) Dressing of Pit and Dry stone pitching 200 mm thick including supply of stones and preparing surface complete. C) Providing and laying in position cement concrete of M-10 grade of 75 mm thickness D) Reinforcement for R.C.C. work with TMT bars including straightening, cutting, bending, placing in position and binding all complete. E) Centring and shuttering including strutting , propping etc. and removal of form work for Footing and Pedestal F) Providing & Fixing of 2 no. Required Size PLB HDPE Pipe & Foundation Bolt with template as per OEM Recommendations. G) Providing and Laying Reinforce cement Concrete of M-25 grade in Footing and Pedestal including Curing the foundation for 7 days. H) Providing and Fixing Nosing Angle 40 | | | | | |
| | 67.8.2 | Pole Foundation for Octagonal pole from 7 Mtr. To 9 Mtr. | 16 | Nos | 8,142.00 | Each | 130272 |
| 3 | 67.2 | Supply and Fixing of Pole OEM fabricated hot dipped galvanised M.S. Overhang (48.3 X 3.25 mm) with cap (400 x 88.9 / 114.3 x 3.25 mm) over the existing poles. All as per pre approved by Engineer in-charge. For additional technical parameters of products/ work , refer Annexure "A" attached with this BSR . | | | | | |
| | 67.2.2 | Double arm overhang | 16 | Mtr | 3,397.00 | Each | 54352 |
| 4 | 67.12 | Providing & Fixing of IK08, IP 66 protected LED Street Light Luminaire on existing bracket/pole. Fixture made of powder coated single piece pressure die cast aluminum material with heat dissipation fins on housing with UV stabilized PC (UV stablization report submitted for UV cover)/Toughened Glass cover and secondary lens on each LED & should be SMD type of 3 to 5 watt each . The System efficacy >=125 lm/ wt and potted driver & has a unique BIS R number with Input Voltage AC 120 to 270 V AC with High voltage Cutoff @>=300 V AC and Auto resetting Safety , Power Factor >0.95 driver Efficiency >85% .THD(I) <10% Humidity 10% to 90% RH Working Temp - 5C to 45C . driver current <750mA. The luminaire shall be BIS certified and Trade mark certified. Life Expectancy Equal or more than 50000 burning hrs with Minimum 70% lumen maintained , CRI >70 and CCT 5700K +355K. Surge protection shall be min ≥ 4 KV internal and min 10 KV external inside driver compartment. driver should be Phase to phase protection of 440 V for 4 Hrs. Manufactures Word Mark/Name Engraved/Embossing on die cast housing to allow traceability/authenticity. Fixture shall be AS PER IS 10322 | | | | | |
| | 67.12.5 | LED Street Light fixture with Minimum lumen output 8700 lm | 32 | Nos | 5,993.00 | Each | 191776 |
| 5 | 60.2 | Providing & Laying P.V.C. / XLPE insulated & P.V.C. sheathed Armoured Aluminium cable conforming to IS:1554 P-1 / IS :7098 P - 1 of 11 KV with H4-Grade electrolytic aluminium conductor conforming to IS 8130 of purity >99.6 % , round / flat strip armouring of cables. Inner / outer sheath conforming to | | | | | |
| | 60.2.3 | 10.0 Sq. mm | | | | | |
| | 60.2.3.3 | 4 core | 400 | Mtr | 197.00 | Each | 78800 |

Handwritten signature

| | | | | | | | |
|-------------------------|---------------|--|-----|-----|--------|------|-----------|
| 6 | 50.4 | S&F following sizes (dia.) of ISI marked virgin material MMS (IS:9537 P - III) PVC conduit along with ISI marked (IS:3419-1988) accessories as required in recess including cutting the wall, covering conduit and making good the same as required. For additional technical parameters of product / work refer Annexure 'A' attached with this BSR | 400 | Mtr | 118.00 | Each | 47200 |
| 7 | 53.1 | 40 mm Supplying and drawing FR PVC insulated & unsheathed flexible copper conductor as per PWD specification for electrical Works with ISI marked (IS:694) and as per IS 8130 : 2013 of 1.1 kV grade. Wire should be made from 99.90 % purity copper, class 5 stranding in acc. to IS:8130/IEC 60228 for lower watt loss, oxygen free for less chances of oxidization, insulation PVC type A/C/D, flame retardant as per IS 10810-53, better amperage rating as per IS:3961 part 5, in existing surface or recessed PVC/MS conduit/casing capping making connections with Copper Lugs of suitable size. Ferrules, testing etc. as required. OEM Must have its own in house NABL lab setup for all testing facilities for wires. For additional technical parameters of product / work refer Annexure 'A' attached with this BSR | 450 | Mtr | 44 | Each | 19800 |
| 53.1.2 | 2 x 1.5 sq.mm | | | | | | 770520.00 |
| TOTAL G Schedule | | | | | | | |

H SCH

| | | | | | | | |
|-----------------------------|---|---|----|-----|--|------|--|
| S.no. | 1 | Removing of tubular pole in all respect including required site pandestal, iron support etc. Removing pole should be deposited in nigam office /store including loading unloading as per direction of engineering incharge. | 13 | Nos | | Each | |
| | 2 | Removing and refixing of LED lights from existing site as per direction of engineering incharge | 24 | Nos | | Each | |
| TOTAL H Schedule | | | | | | | |
| TOTAL (G+H) Schedule | | | | | | | |

[Signature]
XEN(Elect)
JMC

I agree to do above "G" Schedule work Above/ Below RUIDP 2022 and JMC terms and conditions..
and H Sch. @ 1 item.....each
and H Sch. @ 2 itemeach

Signature of Contractor

Jodhpur Municipal Corporation (South), Jodhpur

Name of work:-

Renovation work of various park in ward 38 to 80 nagar nigam south jodhpur.

RUIDP-2023


| S.no. | CODE no | Schedule) PARTICULARS | ("G" Schedule) | | | | |
|-------|----------|--|----------------|------|----------|------|--------|
| | | | QTY. | | RATE | | AMOUNT |
| 1 | 60.2 | Providing & Laying P.V.C / XLPE insulated & P.V.C. sheathed Armoured Aluminium cable conforming to IS 1554 P-1 / IS : 7098 P - 1 of 1.1 kV with H4-Grade electrolytic aluminium conductor conforming to IS 8130 of purity >99.6 %, round / flat strip armouring of cables, Inner / outer sheath conforming to IS:5831 in existing RCC / Hume / Stoneware / PVC pipe/ open duct/cable trench / Cable tray(with cable tie) including testing etc. as required of following size. OEM must have it's own in house NABL accredited Laboratory for testing procedure as per IS 10810.For additional technical parameters of product / work refer Annexure 'A' attached with this BSR | | | | | |
| | 60.2.3 | 10.0 Sq. mm | | | | | |
| | 60.2.2.3 | 4 core | 2500 | Mtr | 197.00 | Each | 492500 |
| | 60.2.2 | 6.0 Sq. mm | | | | | |
| | 60.2.2.1 | 2 core | 1000 | Mtr | 131.00 | Each | 131000 |
| 2 | 50.4 | S&F following sizes (dia.) of ISI marked virgin material MMS (IS 9537 P - III) PVC conduit along with ISI marked (IS.3419-1988) accessories as required in recess including cutting the wall, covering conduit and making good the same as required. For additional technical parameters of product / work refer Annexure 'A' attached with this BSR | | | | | |
| | 50.4.4 | 40 mm | 2000 | Mtr | 118.00 | Each | 236000 |
| 3 | 53.6 | Supply & drawing Wiring for sub mains ISI marked (IS:694) 1100 Volts grade PVC insulated flat twin core sheathed solid aluminium conductor with 10 SWG G.I. Support wire duly clipped etc. as required. For additional technical parameters of product / work refer Annexure 'A' attached with this BSR | | | | | |
| | 53.6.1 | 4.0 sq.mm | 500 | Mtr. | 62.00 | Each | 31000 |
| 4 | 67.1 | Supply and erection of Galvanized Iron pole with galvanizing done in single dipping (Average coating thickness Minimum 65 Microns) continuously tapered poles having Octagonal / Circular cross-sections designed to withstand the maximum wind speed as per IS 875, The pole shaft shall be made from sheet steel (HT Steel conforming to grade S355JO) and conforming to BSEN 10025 and shall be continuously tapered with single longitudinal welding. There shall not be any circumferential welding. The welding of pole shaft shall be done by Submerged Arc Welding (SAW) process. pole shafts shall be provided with the rigid flange plate of suitable thickness (Fe 410 conforming to IS 226 / IS 2062) with provision for fixing 4 no. foundation bolts, This base plate shall be fillet welded to the pole shaft at two locations i.e. from inside and outside.The octagonal Poles shall have lockable door of approximate 500 mm length at the elevation of 500 mm from the Base plate with bakelite sheet having 6A SP MCB and 16 sqmm stud type connector (4 nos) inside the pole at door opening for cable connection of following length and dimension as per table P-01 with base plate and foundation bolt on the Existing cement concrete foundation.All as per pre approved by Engineer in-charge. For additional technical parameters of products/ work , refer Annexure "A" attached with this BSR . | | | | | |
| | 67.1.1 | Poles with Octagonal Cross Section | | | | | |
| | 67.1.1.2 | 4 Mtr. | 20 | Nos | 8,001.00 | Each | 160020 |
| 5 | 67.1 | Providing & Fixing of IK08 IP65 protected Top/Bottom mounted LED Post top Luminarie made of single piece construction powder coated die cast aluminium housing with UV stabalized Clear / frosted Polycarbonate diffuser and Aluminium anodised with sand blast reflector. The System level Luminous efficacy ≥ 100 Lumen/W. SMD LEDs is to be used, System CRI>70, CCT: 3000/4000/6500 K. The integral electronic driver must be potted & has a unique BIS R number must be potted & has a unique BIS R number constant current and Internal/external surge protection device of min. 4KV(L-N) and efficiency > 85%, PF>0.9. THD<10% and input Voltage range of 140-270V AC at 50Hz. System life of 50000 Burning hours with 70% of Initial Lumens maintained . Driver current <750mA. Fixture must be in compliance with BIS Standards and Trade mark Certificate complete in all respect.OEM Must have its own in house NABL lab setup for all testing facilities for LED fixtures. (LM79/LM80) Certificate/ report with liable warranty of product/accessories from OEM shall be submitted. All as per pre approved by Engineer in-charge. For additional technical parameters of products/ work , refer Annexure "A" attached with this BSR . | | | | | |
| | 67.10.1 | Minimum lumen output 2500 lm Post top Luminarie | 40 | Nos | 5,202.00 | Each | 208080 |

Handwritten signature

Name of work:-
RUIDP-2023
Supply and

| S.no. | CODE no |
|-------|---------|
| 1 | 67.1 |

| | | | | | | | |
|-----------------------------|---------|--|----|-----|----------|------|-------------------|
| 6 | 67.8 | Providing and Laying RCC Foundation for Octagonal / Conical Street Light poles, High mast Poles as per Drawing attach at Table P-4 with Following Procedure & All as per pre approved by Engineer in-charge. For additional technical parameters of products/ work , refer Annexure "A" attached with this BSR . A) Excavation of Pit for Foundation Size upto required depth from Ground level B) Dressing of Pit and Dry stone pitching 200 mm thick including supply of stones and preparing surface complete. C) Providing and laying in position cement concrete of M-10 grade of 75 mm thickness D) Reinforcement for R.C.C. work with TMT bars including straightening, cutting, bending, placing in position and binding all complete E) Centring and shuttering including strutting , propping etc. and removal of form work for Footing and Pedestal F) Providing & Fixing of 2 no. Required Size PLB HDPE Pipe & Foundation Bolt with template as per OEM Recommendations. G) Providing and Laying Reinforce cement Concrete of M-25 grade in Footing and Pedestal including Curing the foundation for 7 days H) Providing and Fixing Nosing Angle 40 mm x 40 mm x 6mm with 2 no. 100 mm long, 10 mm dia. Lugs on each face. | | | | | |
| | 67.8.1 | Pole Foundation for Octagonal pole from 3 Mtr. To 6 Mtr. | 20 | Nos | 5,973.00 | Each | 119460 |
| | 67.17 | Providing and fixing of IP 65 protected Polycarbonate / Polyesterene fuse box moulded with inside knock outs of following size with hinged cover, transparent window, PU gasket, locking arrangement, duly holded with 2 nos. pole clamps of 20 mm x 3 mm flat with nut and bolts, The box shall be provided with Din rail, 4 / 8 way 10.0 / 16.0 sq.mm heavy duty connector, earth terminal, complete in all respect. All as per pre approved by Engineer in-charge. For additional technical parameters of products/ work , refer Annexure "A" attached with this BSR . | | | | | |
| | 67.17.1 | 125 mm X 200 mm X 122 mm | 20 | Nos | 1,873.00 | Each | 37460 |
| TOTAL G Schedule | | | | | | | 1415520.00 |
| H Schedule item | | | | | | | |
| S.no. | 1 | Removing , repairing and refixing of existing Decorative pole including proper foundation and deposit unused material as per direction of engineering incharge. and | 40 | Nos | | Each | |
| | 2 | Colouring of existing Decorative , Tubular pole with proper redoxide and Enamel Colour as per direction of engineering incharge. | 40 | Nos | | Each | |
| TOTAL H Schedule | | | | | | | |
| TOTAL G + H Schedule | | | | | | | |


XEN(Elect)
JMC

I agree to do above "G" Schedule work Above/ Below RUIDP 2022 and JMC terms and conditions..
and H Sch. @ 1 item.....each
and H Sch. @ 2 itemeach

Signature of Contractor

Jodhpur Municipal Corporation (South), Jodhpur

3

Name of work:-

Supply and fixing LED and SHM in ward 45 nagar nigam south jodhpur.

RUIDP-2023

| S.no. | CODE no | PARTICULARS | ("G" Schedule) | | |
|-------|---------|--|----------------|------|-----------|
| | | | QTY. | RATE | AMOUNT |
| 1 | 67.1 | Supply and erection of Galvanized Iron pole with galvanizing done in single dipping (Average coating thickness Minimum 65 Microns) continuously tapered poles having Octagonal / Circular cross-sections designed to withstand the maximum wind speed as per IS 875. The pole shaft shall be made from sheet steel (HT Steel Conforming to grade S355JO) and conforming to BSEN 10025 and shall be continuously tapered with single longitudinal welding. There shall not be any circumferential welding. The welding of pole shaft shall be done by Submerged Arc Welding (SAW) process. pole shafts shall be provided with the rigid flange plate of suitable thickness (Fe 410 conforming to IS 226 / IS 2062) with provision for fixing 4 no. foundation bolts, This base plate shall be fillet welded to the pole shaft at two locations i.e. from inside and outside. The octagonal Poles shall have lockable door of approximate 500 mm length at the elevation of 500 mm from the Base plate with bakelite sheet having 6A SP MCB and 16 sqmm stud type connector (4 nos) inside the pole at door opening for cable connection of following length and dimension as per table P-01 with base plate and foundation bolt on the Existing cement concrete foundation. All as per pre approved by Engineer in-charge. For additional technical parameters of products/ work , refer Annexure "A" attached with this BSR . | | | |
| | 67.1.1 | Poles with Octagonal Cross Section | | | |
| | 67.1.6 | 8 Mtr. | 3 | Nos | 15,520.00 |
| | | | | Each | 46560.00 |
| 2 | 67.8 | Providing and Laying RCC Foundation for Octagonal / Conical Street Light poles, High mast Poles as per Drawing attach at Table P-4 with Following Procedure & All as per pre approved by Engineer in-charge. For additional technical parameters of products/ work , refer Annexure "A" attached with this BSR A) Excavation of Pit for Foundation Size upto required depth from Ground level B) Dressing of Pit and Dry stone pitching 200 mm thick including supply of stones and preparing surface complete. C) Providing and laying in position cement concrete of M-10 grade of 75 mm thickness D) Reinforcement for R.C.C. work with TMT bars including straightening, cutting, bending, placing in position and binding all complete. E) Centring and shuttering including strutting , propping etc. and removal of form work for Footing and Pedestal F) Providing & Fixing of 2 no. Required Size PLB HDPE Pipe & Foundation Bolt with template as per OEM Recommendations. G) Providing and Laying Reinforce cement Concrete of M-25 grade in Footing and Pedestal including Curing the foundation for 7 days. H) Providing and Fixing Nosing Angle 40 mm x 40 mm x 6mm with 2 no. 100 mm long, 10 mm dia Lugs on each face. | | | |
| | 67.8.2 | Pole Foundation for Octagonal pole from 7 Mtr. To 9 Mtr. | 3 | Nos | 8,142.00 |
| | | | | Each | 24426.00 |
| 3 | 67.2 | Supply and Fixing of Pole OEM fabricated hot dipped galvanized MS Overhang (48.3 X 3.25 mm) with cap (400 x 88.9 / 114.3 x 3.25 mm) over the existing poles. All as per pre approved by Engineer in-charge. For additional technical parameters of products/ work , refer Annexure "A" attached with this BSR . | | | |
| | 67.2.2 | Double arm overhang | 6 | Mtr | 3,397.00 |
| | | | | RM | 20382.00 |
| 4 | 67.11 | Providing & Fixing of IK08 IP-66 protected high power LED flood light system with single piece Pressure diecast aluminium housing, toughened glass diffuser with suitable lenses on LED to achieve various beam angles, of high power LED of 3 to 5 watt each . Integrated potted driver as a unique BIS R number having efficiency more than 85 % and in compliance to BIS certified and Trade mark certificate The System level Luminaire efficacy >=125 lm/ wt. LED driver Input Voltage AC 120 to 270 V AC with High voltage Cutoff <i>i> >= 300 V AC and Auto resetting Safety Power Factor >0.95 , THD(I) <10% , driver current <=750mA driver should be Phase to phase protection of 440 V for 4 Hrs Electrical Connector , Surge Protection Min >=4KV internal and 10KV external but inside driver compartment, System life of 50000 Burning hours with 70% of Initial Lumens maintained, CRI>70 and CCT 5700K ±355K. Manufactures Word Mark/Name Engraved/Embossing/Screen printing on die cast housing to allow traceability/authenticity Fixture shall be IS 10322 Complanced OEM Must have its own in house NABL lab setup for all testing facilities for LED fixtures | | | |
| | 67.11.5 | High Power LED Flood Light Minimum lumen output 12400 lm | 12 | Nos | 6,048.00 |
| | | | | Each | 72576.00 |

Name of work: RUIDP

| | | | | | | | |
|-------------------------|----------|--|-----|------|----------|------|------------------|
| 5 | 67.12 | Providing & Fixing of IK08, IP 66 protected LED Street Light Luminaire on existing bracket/pole. Fixture made of powder coated single piece pressure die cast aluminum material with heat dissipation fins on housing with UV stabilized PC (UV stabilization report submitted for UV cover) /Toughened Glass cover and secondary lens on each LED & should be SMD type of 3 to 5 watt each. The System efficacy >=125 lm/ wt and potted driver & has a unique BIS R number with Input Voltage AC 120 to 270 V AC with High voltage Cutoff @>=300 V AC and Auto resetting Safety, Power Factor >0.95 driver Efficiency >85%, THD(1) <10% Humidity 10% to 90% RH Working Temp -5C to 45C driver current <750mA. The luminaire shall be BIS certified and Trade mark certified. Life Expectancy Equal or more than 50000 burning hrs with Minimum 70% lumen maintained, CRI >70 and CCT 5700K +355K. Surge protection shall be min ≥ 4 KV internal and min 10 KV external inside driver compartment. driver should be Phase to phase protection of 440 V for 4 Hrs. Manufactures Word Mark/Name Engraved/Embossing on die cast housing to allow traceability/authenticity. Fixture shall be AS PER IS 10322 Complied OEM Must have its own in house NABL lab setup for all testing facilities for LED fixtures. (LM79/LM80) Certificate/report with liable warranty of product/accessories from OEM shall be submitted. All as per pre approved by Engineer in-charge. For additional technical parameters of products/ work, refer Annexure "A" attached with this BSR. | | | | | |
| | 67.12.3 | LED Street Light fixture with Minimum lumen output 5600 lm | 25 | Nos | 4,249.00 | Each | 106225.00 |
| | 67.12.5 | LED Street Light fixture with Minimum lumen output 8700 lm | 45 | Nos | 5,993.00 | Each | 269685.00 |
| 6 | 67.18 | Providing & Fixing of Street light bracket made out from following size of 'B' class. Medium class G.I. Pipe conforming to IS : 1239 P-1 (2004) with heavy duty pole clamp, Saddles suitable fastners etc. as required. All as per pre approved by Engineer in-charge. For additional technical parameters of products/ work, refer Annexure "A" attached with this BSR | | | | | |
| | 67.18.3 | 32 mm Dia. | 70 | Mtr. | 761.00 | Each | 53270.00 |
| 7 | 60.2 | Providing & Laying P.V.C. / XLPE insulated & P.V.C. sheathed Armoured Aluminium cable conforming to IS:1554 P-1 / IS :7098 P-1 of 1.1 KV with H4- Grade electrolytic aluminium conductor conforming to IS 8130 of purity >99.6 %, round / flat strip armouring of cables, Inner / outer sheath conforming to IS:5831 in existing RCC / Hume / Stoneware / PVC pipe/ open duct/cable trench / Cable tray(with cable tie) including testing etc. as required of following size. OEM must have it's own in house NABL accredited Laboratory for testing procedure as per IS:10810.For additional technical parameters of product / work refer Annexure 'A' attached with this BSR | | | | | |
| | 60.2.3 | 10.0 Sq. mm | | | | | |
| | 60.2.3.3 | 4 core | 50 | Mtr | 197.00 | Each | 9850.00 |
| | 60.2.2 | 6.0 Sq. mm | | | | | |
| | 60.2.2.1 | 2 core | 100 | Mtr | 131.00 | Each | 13100.00 |
| 8 | 53.6 | Supply & drawing Wiring for sub mains ISI marked (IS:694) 1100 Volts grade PVC insulated flat twin core sheathed solid aluminium conductor with 10 SWG G.I. Support wire duly clipped etc. as required. For additional technical parameters of product / work refer Annexure 'A' attached with this BSR | | | | | |
| | 53.6.1 | 4.0 sq mm | 300 | Mtr | 62.00 | Each | 18600.00 |
| TOTAL G Schedule | | | | | | | 634674.00 |
| Say | | | | | | | 634674.00 |

[Signature]
XEN(Elect)
JMC

I agree to do above "G" Schedule work Above/ Below RUIDP 2022 and JMC terms and conditions..

signature of contractor

Jodhpur Municipal Corporation (South), Jodhpur

(21)

Name of work:- **Supply and fixing LED and SHM in ward 37 in nagar nigam south jodhpur.**

RUIDP-2023

| Schedule | | PARTICULARS | ("G" Schedule) | | | | |
|----------|---------|---|----------------|------|-----------|------|--------|
| S.no. | CODE no | | QTY. | RATE | AMOUNT | | |
| 1 | 67.1 | Supply and erection of Galvanized Iron pole with galvanizing done in single dipping (Average coating thickness Minimum 65 Microns) continuously tapered poles having Octagonal / Circular cross-sections designed to withstand the maximum wind speed as per IS 875. The pole shaft shall be made from sheet steel (HT Steel Conforming to grade S355JO) and confirming to BSEN 10025 and shall be continuously tapered with single longitudinal welding. There shall not be any circumferential welding. The welding of pole shaft shall be done by Submerged Arc Welding (SAW) process. pole shafts shall be provided with the rigid flange plate of suitable thickness (Fe 410 conforming to IS 226 / IS 2062) with provision for fixing 4 no. foundation bolts. This base plate shall be fillet welded to the pole shaft at two locations i.e. from inside and outside. The octagonal Poles shall have bakelite sheet having 6A SP MCB and 16 sqmm studs type connector (4 nos) inside the pole at door opening for cable connection of following length and dimension as per table P-01 with base plate and foundation bolt on the Existing concrete foundation. All as per pre approved by Engineer in-charge. For additional Poles with Octagonal Cross Section | 5 | Nos | 15,520.00 | Each | 77600 |
| | 67.1.1 | 8 Mtr. | | | | | |
| | 67.1.6 | Providing and Laying RCC Foundation for Octagonal / Conical Street Light poles, right must by Engineer in-charge. For additional technical parameters of products/ work, refer Annexure "A" attached with this BSR. | | | | | |
| 2 | 67.8 | A) Excavation of Pit for Foundation Size upto required depth from Ground level B) Dressing of Pit and Dry stone pitching 200 mm thick including supply of stones and preparing surface complete. C) Providing and laying in position cement concrete of M-10 grade of 75 mm thickness D) Reinforcement for R.C.C. work with TMT bars including straightening, cutting, bending, placing in position and binding all complete. E) Centring and shuttering including strutting, propping etc. and removal of form work for Footing and Pedestal F) Providing & Fixing of 2 no. Required Size PLB HDPE Pipe & Foundation Bolt with template as per OEM Recommendations. G) Providing and Laying Reinforce cement Concrete of M-25 grade in Footing and Pedestal including Curing the foundation for 7 days. H) Providing and Fixing Nosing Angle 40 mm x 40 mm x 6mm with 2 no. 100 mm long, 10 mm dia. Lugs on each face. | 5 | Nos | 8,142.00 | Each | 40710 |
| | 67.8.2 | Pole Foundation for Octagonal pole from 7 Mtr. To 9 Mtr. | | | | | |
| 3 | 67.2 | Supply and Fixing of Pole OEM fabricated hot dipped galvanised M.S. Overhang (48.3 X 3.25 mm) with cap (400 x 88.9 / 114.3 x 3.25 mm) over the existing poles. All as per pre approved by Engineer in-charge. For additional technical parameters of products/ work, refer Annexure "A" attached with this BSR. | 10 | Mtr | 3,397.00 | RM | 33970 |
| | 67.2.2 | Double arm overhang | | | | | |
| 4 | 67.11 | Providing & Fixing of IK05 IP-66 protected high power LED flood light system with single piece Pressure diecast aluminium housing, toughened glass diffuser with suitable lenses on LED driver as a unique BIS R number having efficiency more than 85 % and in compliance to BIS certified and Trade mark certificate. The System level Luminaire efficacy >=125 lm/ wt. LED driver Input Voltage AC 120 to 270 V AC with High voltage Cutoff @>=300 V AC and Auto resetting Safety. Power Factor >0.95, THD(I) <10%, driver current <=750mA. driver should be Phase to phase protection of 440 V for 4 Hrs. Electrical Connector, Surge Protection Min >=4KV internal and 10KV external but inside driver compartment, System life of 50000 Burning hours with 70% of Initial Lumens maintained, CRI>70 and CCT 5700K ±355K. Manufactures Word Mark/Name Engraved/Embossing/Screen printing on die cast housing to allow traceability/authenticity. Fixture shall be IS 10322 Complianced.OEM Must have its own in house NABL lab setup for all testing facilities for LED fixtures. (LM79/LM80) Certificate/ report with liable warranty of product/accessories from OEM shall be submitted. All as per pre | 20 | Nos | 9,094.00 | Each | 181880 |
| | 67.11.6 | High Power LED Flood Light Minimum lumen output 14800 lm | | | | | |
| 5 | 67.12 | Providing & Fixing of IK05 IP-66 protected LED Street Light Luminaire on existing bracket/pole. Fixture made of powder coated single piece pressure die cast aluminum material with heat dissipation fins on housing with UV stabilized PC (UV stabilization report submitted for UV cover) /Toughened Glass cover and secondary lens on each LED & should be SMD type of 3 to 5 watt each. The System efficacy >=125 lm/ wt and potted driver & has a unique BIS R number with Input Voltage AC 120 to 270 V AC with High voltage Cutoff @>=300 V AC and Auto resetting Safety, Power Factor >0.95 driver Efficiency >85%, THD(I) <10% Humidity 10% to 90% RH Working Temp -5C to 45C. driver current <750mA. The luminaire shall be BIS certified and Trade mark certified. Life Expectancy Equal or more than 50000 protection shall be min ≥ 4 KV internal and min 10 KV external inside driver compartment. driver should be Phase to phase protection of 440 V for 4 Hrs. Manufactures Word Mark/Name Engraved/Embossing on die cast housing to allow traceability/authenticity. Fixture shall be AS PER IS 10322 Complianced.OEM Must have its own in house NABL lab setup for all testing | 28 | Nos | 4,249.00 | Each | 118972 |
| | 67.12.3 | LED Street Light fixture with Minimum lumen output 5600 lm | 25 | Nos | 5,993.00 | Each | 149825 |
| | 67.12.5 | LED Street Light fixture with Minimum lumen output 8700 lm | | | | | |
| 6 | 67.18 | Providing & Fixing of Street light bracket made out from following size of 'B' class, Medium class G.I. Pipe conforming to IS : 1239 P - 1 (2004) with heavy duty pole clamp, Saddles suitable fasteners etc. as required. All as per pre approved by Engineer in-charge. For additional technical parameters of products/ work, refer Annexure "A" attached with this BSR. | 53 | Mtr | 761 | Each | 40333 |
| | 67.18.3 | 32 mm Dia. | | | | | |

Jodhpur Municipal Corporation (South), Jodhpur

Name of work:-

Supply and fixing LED and SHM in ward 37 in nagar nigam south jodhpur.

RUIDP-2023

| Schedule | | ("G" Schedule) | | | | | |
|-------------------------|----------|--|------|-----|------|--------|-----------|
| S.no. | CODE no | PARTICULARS | QTY. | | RATE | AMOUNT | |
| 7 | 60.2 | Providing & Laying P.V.C. / XLPE insulated & P.V.C. sheathed Armoured Aluminium cable confirming to IS:1554 P-1 / IS :7098 P - 1 of 1.1 KV with H4- Grade electrolytic aluminium conductor confirming to IS 8130 of purity >99.6 %, round / flat strip armouring of cables, Inner / outer sheath confirming to IS:5831 in existing RCC / Hume / Stoneware / PVC pipe/ open duct/cable trench / Cable tray(with cable tie) including testing etc. as required of following size. OEM must have it's own in house NABL accredited Laboratory for testing procedure as per IS:10810.For additional technical parameters of product / work refer Annexure 'A' attached with this BSR | | | | | |
| | 60.2.3 | 10.0 Sq. mm | | | | | |
| | 60.2.3.3 | 4 core | 150 | Mtr | 197 | Each | 29550 |
| 8 | 50.4 | S&F following sizes (dia.) of ISI marked virgin material MMS (IS:9537 P - III) PVC conduit along with ISI marked (IS:3419-1988) accessories as required in recess including cutting the wall, covering conduit and making good the same as required. For additional technical parameters of product / work refer Annexure 'A' attached with this BSR | | | | | |
| | 50.4.4 | 40 mm | 100 | Mtr | 118 | Each | 11800 |
| 9 | 53.1 | Supplying and drawing FR PVC insulated & unsheathed flexible copper conductor as per PWD specification for electrical Works with ISI marked (IS:694) and as per IS 8130 : 2013 of 1.1 kV grade . Wire should be made from 99.90 % purity copper, class 5 stranding in acc. to IS:8130/IEC 60228 for lower watt loss , oxygen free for less chances of oxidization, insulation PVC type A/C/D , flame retardant as per IS 10810-53, better amperage rating as per IS:3961 part 5, in existing surface or recessed PVC/ MS conduit/casing capping making connections with Copper Lugs of suitable size, Ferrules,testing etc. as required. OEM Must have its own in house NABL lab setup for all testing facilities for wires. For additional technical parameters of product / work refer Annexure 'A' attached with this BSR | | | | | |
| | 53.1.2 | 2 x 1.5 sq.mm | 350 | Mtr | 44 | Each | 15400 |
| TOTAL G Schedule | | | | | | | 700040.00 |
| Sav | | | | | | | 7.0 lac |

(Signature)
XEN(Elect)
JMC

I agree to do above "G" Schedule work @ above/below on RUIDP 2023 electric with JMC terms and conditions..

Signature of Contractor

Jodhpur Municipal Corporation (South), Jodhpur

Supply and fixing of LED street lights at various location in Soorsagar Assembly Area(ward 1 to 37) as per demand.

Name of work:-

RUIDP-2023

| Sn. | CODE No | PARTICULARS | ("G" Schedule) | | | AMOUNT | |
|-------------------------|---------|--|----------------|------|----------|--------|---------------|
| | | | QTY. | RATE | | | |
| 1 | 67.12 | Providing & Fixing of IK08, IP 66 protected LED Street Light Luminaire on existing bracket/pole. Fixture made of powder coated single piece pressure die cast aluminum material with heat dissipation fins on housing with UV stabilized PC (UV stablization report submitted for UV cover)/Toughened Glass cover and secondary lens on each LED & should be SMD type of 3 to 5 watt each . The System efficacy >=125 lm/ wt and potted driver & has a unique BIS R number with Input Voltage AC 120 to 270 V AC with High voltage Cutoff @>=300 V AC and Auto resetting Safety , Power Factor >0.95 driver Efficiency >85% ,THD(I) <10% Humidity 10% to 90% RH Working Temp -5C to 45C . driver current <750mA. The luminaire shall be BIS certified and Trade mark certified. Life Expectancy Equal or more than 50000 burning hrs with Minimum 70% lumen maintained , CRI >70 and CCT 5700K +355K. Surge protection shall be min ≥ 4 KV internal and min 10 KV external inside driver compartment. driver should be Phase to phase protection of 440 V for 4 Hrs. Manufactures Word Mark/Name Engraved/Embossing on die cast housing to allow traceability/authenticity. Fixture shall be AS PER IS 10322 Complianced.OEM Must have its own in house NABL lab setup for all testing facilities for LED fixtures. (LM79/LM80) Certificate/ report with liable warranty of product/accessories from OEM shall be submitted. All as per pre approved by Engineer in-charge. For additional technical parameters of products/ work , refer Annexure "A" attached with this BSR . | | | | | |
| | | | 250 | Nos | 5,993.00 | Each | 1498250 |
| | | | 250 | Nos | 8,941.00 | Each | 2235250 |
| | 67.12.5 | LED Street Light fixture with Minimum lumen output 8700 lm | | | | | |
| | 67.12.8 | LED Street Light fixture with Minimum lumen output 15000 lm | | | | | |
| 2 | 67.18 | Providing & Fixing of Street light bracket made out from following size of 'B' class , Medium class G.I. Pipe conforming to IS : 1239 P - 1 (2004) with heavy duty pole clamp, Saddles suitable fastners etc. as required. All as per pre approved by Engineer in-charge. For additional technical parameters of products/ work , refer Annexure "A" attached with this BSR . | | | | | |
| | | | 500 | Mtr | 761 | Each | 380500 |
| | 67.18.3 | 32 mm Dia. | | | | | |
| 3 | 53.6 | Supply & drawing Wiring for sub mains ISI marked (IS:694) 1100 Volts grade PVC insulated flat twin core sheathed solid aluminium conductor with 10 SWG G.I. Support wire duly clipped etc. as required. For additional technical parameters of product / work refer Annexure 'A' attached with this BSR | | | | | |
| | | | 1300 | Mtr | 62 | Each | 80600 |
| | 53.6.1 | 4.0 Sq. mm 2 core | | | | | 4194600.00 |
| TOTAL G Schedule | | | | | | | 42.00L |
| Say | | | | | | | |

[Signature]

XEN(Elect)
JMC

I agree to do above "G" Schedule work @ above/below on RUIDP 2023 electric with JMC terms and conditions..

Signature of Contractor

Jodhpur Municipal Corporation (South), Jodhpur

Name of work:-
RUIDP-2023

Supply and fixing of LED street lights instead of sodium lights in Soorsagar Assembly Area jodhpur as per demand. in
(ward 1 to 37) NNJ South.

| Sn. | CODE No | Schedule PARTICULARS | ("G" Schedule) | | | | |
|-------------------------|---------|---|----------------|------|----------|------|-------------------|
| | | | QTY. | RATE | AMOUNT | | |
| 1 | 67.12 | Providing & Fixing of IK08, IP 66 protected LED Street Light Luminaire on existing bracket/pole. Fixture made of powder coated single piece pressure die cast aluminum material with heat dissipation fins on housing with UV stabilized PC (UV stablization report submitted for UV cover) /Toughened Glass cover and secondary lens on each LED & should be SMD type of 3 to 5 watt each . The System efficacy >=125 lm/ wt and potted driver & has a unique BIS R number with Input Voltage AC 120 to 270 V AC with High voltage Cutoff @>=300 V AC and Auto resetting Safety , Power Factor >0.95 driver Efficiency >85% ,THD(I) <10% Humidity 10% to 90% RH Working Temp -5C to 45C . driver current <750mA. The luminaire shall be BIS certified and Trade mark certified. Life Expectancy Equal or more than 50000 burning hrs with Minimum 70% lumen maintained , CRI >70 and CCT 5700K +355K. Surge protection shall be min ≥ 4 KV internal and min 10 KV external inside driver compartment. driver should be Phase to phase protection of 440 V for 4 Hrs. Manufactures Word Mark/Name Engraved/Embossing on die cast housing to allow traceability/authenticity. Fixture shall be AS PER IS 10322 Complianced.OEM Must have its own in house NABL lab setup for all testing facilities for LED fixtures. (LM79/LM80) Certificate/ report with liable warranty of product/accessories from OEM shall be submitted. All as per pre approved by Engineer in-charge. For additional technical parameters of products/ work , refer Annexure "A" attached with this BSR . | | | | | |
| | 67.12.8 | LED Street Light fixture with Minimum lumen output 15000 lm | 370 | Nos | 8,941.00 | Each | 3308170 |
| 2 | 67.11 | Providing & Fixing of IK08 IP-66 protected high power LED flood light system with single piece Pressure diecast aluminium housing, toughened glass diffuser with suitable lenses on LED to achieve various beam angles, of high power LED of 3 to 5 watt each . Integrated potted driver as a unique BIS R number having efficiency more than 85 % and in compliance to BIS certified and Trade mark certificate. The System level Luminaire efficacy >=125 lm/ wt. LED driver Input Voltage AC 120 to 270 V AC with High voltage Cutoff @>=300 V AC and Auto resetting Safety .Power Factor >0.95 , THD(I) <10% , driver current <=750mA. driver should be Phase to phase protection of 440 V for 4 Hrs. Electrical Connector , Surge Protection Min >=4KV internal and 10KV external but inside driver compartment, System life of 50000 Burning hours with 70% of Initial Lumens maintained, CRI>70 and CCT 5700K ±355K. Manufactures Word Mark/Name Engraved/Embossing/Screen printing on die cast housing to allow traceability/authenticity. Fixture shall be IS 10322 Complianced.OEM Must have its own in house NABL lab setup for all testing facilities for LED fixtures. (LM79/LM80) Certificate/ report with liable warranty of product/accessories from OEM shall be submitted. All as per pre approved by Engineer in-charge. For additional technical parameters of products/ work , refer Annexure "A" attached with this BSR . | | | | | |
| | 67.11.6 | High Power LED Flood Light Minimum lumen output 14800 lm | 50 | Nos | 9,094.00 | Each | 454700 |
| 3 | 67.18 | Providing & Fixing of Street light bracket made out from following size of 'B' class , Medium class G.I. Pipe conforming to IS : 1239 P - 1 (2004) with heavy duty pole clamp, Saddles suitable fastners etc. as required. All as per pre approved by Engineer in-charge. For additional technical parameters of products/ work , refer Annexure "A" attached with this BSR . | | | | | |
| | 67.18.3 | 32 mm Dia. | 370 | Mtr | 761 | Each | 281570 |
| 5 | 53.6 | Supply & drawing Wiring for sub mains ISI marked (IS:694) 1100 Volts grade PVC insulated flat twin core sheathed solid aluminium conductor with 10 SWG G.I. Support wire duly clipped etc. as required. For additional technical parameters of product / work refer Annexure 'A' attached with this BSR | | | | | |
| | 53.6.1 | 4.0 Sq. mm | 1700 | Mtr | 62 | Each | 105400 |
| | 53.6.3 | 10.0 Sq. mm | 500 | Mtr | 100 | Each | 50000 |
| TOTAL G Schedule | | | | | | | 4199840.00 |
| Say | | | | | | | 42.00L |

[Signature]
XEN(Elect)
JMC

I agree to do above "G" Schedule work @ above/below on RUIDP 2023 electric with JMC terms and conditions..

Signature of Contractor

निविदादाता द्वारा घोषणा

[सा. नि. एवं लेखा नियम 48 (VII)]

मैं/हम घोषणा करता हूँ/करते हैं कि मैंने/हमने जिन मालो/सामानों/उपकरणों के लिये निविदा दी है, उनका/उनके/मैं/हम थोक विक्रेता/सोल वितरक/प्राधिकृत आगर/डोसर/सोल विक्रेता/विपणन एजेंट हूँ/हैं।

यदि यह घोषणा असत्य पायी जाये तो किसी भी अन्य कार्यवाही, जो की जा सकती है, पर प्रतिकूल प्रभाव डाले बिना, मेरी/हमारी प्रतिभूति को पूर्ण रूप में समपूरत कर दिया जा सकेगा तथा निविदा को, जिस सीमा तक उसे स्वीकार किया गया है रद्द किया जा सकेगा।

(निविदादाता के हस्ताक्षर)

Annexure A : Compliance with the Code of Integrity and No Conflict of Interest

Any person participating in a procurement process shall -

- (a) not offer any bribe, reward or gift or any material benefit either directly or indirectly in exchange for an unfair advantage in procurement process or to otherwise influence the procurement process;
- (b) not misrepresent or omit that misleads or attempts to mislead so as to obtain a financial or other benefit or avoid an obligation;
- (c) not indulge in any collusion, Bid rigging or anti-competitive behavior to impair the transparency, fairness and progress of the procurement process;
- (d) not misuse any information shared between the procuring Entity and the Bidders with an intent to gain unfair advantage in the procurement process;
- (e) not indulge in any coercion including impairing or harming or threatening to do the same, directly or indirectly, to any party or to its property to influence the procurement process;
- (f) not obstruct any investigation or audit of a procurement process;
- (g) disclose conflict of interest, if any; and
- (h) disclose any previous transgressions with any Entity in India or any other country during the last three years or any debarment by any other procuring entity.

Conflict of Interest:-

The Bidder participating in a bidding process must not have a Conflict of Interest.

A Conflict of Interest is considered to be a situation in which a party has interests that could improperly influence that party's performance of official duties or responsibilities, contractual obligations, or compliance with applicable laws and regulations.

i. A Bidder may be considered to be in Conflict of Interest with one or more parties in a bidding process if, including but not limited to:

- a. have controlling partners/ shareholders in common; or
- b. receive or have received any direct or indirect subsidy from any of them; or
- c. have the same legal representative for purposes of the Bid; or
- d. have a relationship with each other, directly or through common third parties, that puts them in a position to have access to information about or influence on the Bid of another Bidder, or influence the decisions of the Procuring Entity regarding the bidding process; or
- e. the Bidder participates in more than one Bid in a bidding process. Participation by a Bidder in more than one Bid will result in the disqualification of all Bids in which the Bidder is involved. However, this does not limit the inclusion of the same subcontractor, not otherwise participating as a Bidder, in more than one Bid; or
- f. the Bidder or any of its affiliates participated as a consultant in the preparation of the design or technical specifications of the Goods, Works or Services that are the subject of the Bid; or
- g. Bidder or any of its affiliates has been hired (or is proposed to be hired) by the Procuring Entity as engineer-in-charge/ consultant for the contract.

Doc1

निरीक्षण के द्वारा

Memorandum of Appeal under the Rajasthan Transparency in Public Procurement Act, 2012

Appeal No of
Before the (First / Second Appellate Authority)

1. Particulars of appellant:

- (i) Name of the appellant:
- (ii) Official address, if any:
- (iii) Residential address:

2. Name and address of the respondent(s):

- (i)
- (ii)
- (iii)

3. Number and date of the order appealed against and name and designation of the officer / authority who passed the order (enclose copy), or a statement of a decision, action or omission of the Procuring Entity in contravention to the provisions of the Act by which the appellant is aggrieved:

4. If the Appellant proposes to be represented by a representative, the name and postal address of the representative:

5. Number of affidavits and documents enclosed with the appeal:

| | | | |
|----|-----------------------------------|----|---------|
| 6. | Grounds | of | appeal: |
| | | | |
| | (supported by an affidavit) | | |

| | | |
|----|--------|-------|
| 7. | Prayer | |
| | | |

Place

Date

Appellant's Signature

मिनीराम के वरदार

Annexure B : Declaration by the Bidder regarding Qualifications

Declaration by the Bidder

In relation to my/our Bid submitted to for procurement of in response to their Notice Inviting Bids No..... Dated..... I/we hereby declare under Section 7 of Rajasthan Transparency in Public Procurement Act, 2012, that:

1. I/we possess the necessary professional, technical, financial and managerial resources and competence required by the Bidding Document issued by the Procuring Entity;
2. I/we have fulfilled my/our obligation to pay such of the taxes payable to the Union and the State Government or any local authority as specified in the Bidding Document;
3. I/we are not insolvent, in receivership, bankrupt or being wound up, not have my/our affairs administered by a court or a judicial officer, not have my/our business activities suspended and not the subject of legal proceedings for any of the foregoing reasons;
4. I/we do not have, and our directors and officers not have, been convicted of any criminal offence related to my/our professional conduct or the making of false statements or misrepresentations as to my/our qualifications to enter into a procurement contract within a period of three years preceding the commencement of this procurement process, or not have been otherwise disqualified pursuant to debarment proceedings;
5. I/we do not have a conflict of interest as specified in the Act, Rules and the Bidding Document, which materially affects fair competition;

Date:

Place:

Signature of bidder

Name:

Designation:

Address:

निविदादाता के हस्ताक्षर

Doc1